

Authentication of Bank Notes and Image Classification through Artificial and Convolutional Neural Network

BY

MD. TOUHIDUL ISLAM
ID: 172-25-599

This Report Presented in Partial Fulfillment of the Requirements for the
Degree of Master of Science in Computer Science and Engineering

Supervised By

DR. SHEAK RASHED HAIDER NOORI
Associate Professor and Associate Head
Department of CSE
Daffodil International University



DAFFODIL INTERNATIONAL UNIVERSITY

DHAKA, BANGLADESH

MAY 2018

APPROVAL

This thesis titled “**Authentication of bank notes and image processing through Artificial and Convolutional Neural Network**”, submitted by **Md. Touhidul Islam** to the Department of Computer Science and Engineering, Daffodil International University, has been accepted as satisfactory for the partial fulfillment of the requirements for the degree of M.Sc. in Computer Science and Engineering and approved as to its style and contents. The presentation has been held on May 07, 2018.

BOARD OF EXAMINERS

(Name)

Designation

Department of CSE

Faculty of Computer Science and Engineering

Daffodil International University

Chairman

(Name)

Designation

Department of CSE

Faculty of Computer Science and Engineering

Daffodil International University

Internal Examiner

(Name)

Designation

Department of CSE

Faculty of Computer Science and Engineering

Daffodil International University

Internal Examiner

(Name)

Designation

Department of

University of

External Examiner

DECLARATION

I hereby declare that, this project has been done by only me under the supervision of **Dr. Sheak Rashed Haider Noori, Associate Professor and Associate Head, Department of CSE**, Daffodil International University. I also declare that neither this thesis nor any part of this thesis has been submitted elsewhere for award of any degree or diploma.

Supervised by:

Name
Designation
Department of CSE
Daffodil International University

Submitted by:

Name
ID: 172-25-599
Department of CSE
Daffodil International University

ACKNOWLEDGEMENT

I am really grateful to and wish my profound respect to **Dr. Sheak Rashed Haider Noori, Associate Professor and Associate Head**, Department of CSE, Daffodil International University, Dhaka. Deep Knowledge & keen interest of my supervisor in the field of data mining influenced me to carry out this research. His endless patience, scholarly guidance, continual encouragement, constant and energetic supervision, constructive criticism, valuable advice, reading many inferior drafts and correcting them at all stages have made it possible to complete this thesis.

I would like to express my heartiest gratitude to Dr. Syed Akhter Hossain, Professor, and Head, Department of CSE, for his excellent mentorship and inspiration in the field of Machine Learning and also to other faculty members and the staffs of CSE department of Daffodil International University.

I would like to thank my entire course mates in Daffodil International University, who took part in this discussion while completing the course work.

Finally, I must acknowledge with due respect the constant support and patients of my parents.

ABSTRACT

This paper focuses on two common applications of image processing done with the help of neural network. At first, it gives a solution for detection of counterfeit bank notes using Artificial Neural Network with the structured image dataset of the corresponding bank notes provided by the UCI Machine Learning Repository. In the second part, the emphasis is on solving the unstructured image classification problem through Convolutional Neural Network and using the famous Kaggle dataset. Both problem include a common Artificial Neural Network architecture. However, in the second problem, on top of Artificial Neural Network, two convolutional layers are added. Two classifications discussed here are non-linear in nature and they have some inherent differences. This paper also discuss the common pitfalls and possible improvement techniques in the future implementation of this strategy along with a detailed discussion.

TABLE OF CONTENTS

CONTENS	PAGE
Board of examiners	i
Declaration	ii
Acknowledgements	iii
Abstract	iv

CHAPTER

CHAPTER 1: INTRODUCTION 1-6

1.1 Infrastructure Mode	1
1.2 Motivation	2
1.3 Rationale of the Study	
1.4 Research Questions	
1.5 Expected Outputs	
1.6 Thesis Layout	

CHAPTER 2: BACKGROUND

2.1 Introduction	
2.2 Related Works	
2.3 Research Summary	
2.4 Scope of the Problem	

2.5 Challenges

CHAPTER 3: RESEARCH METHODOLOGIES

3.1 Introduction

3.2 Research Subject and Instrumentation

3.3 Data Collection Procedures

3.4 Statistical Analysis

3.5 Implementation Requirements

CHAPTER 4: EXPERIMENTAL RESULTS AND DISCUSSIONS

4.1 Introduction

4.2 Experimental Results

4.3 Descriptive Analysis

4.4 Summary

CHAPTER 5: CONCLUSION AND RECOMMENDATION

5.1 Summary of the Study

5.2 Conclusion

5.3 Recommendation

5.4 Implication for further study

LIST OF FIGURES

Figure 1 Architecture of Artificial Network

- Figure 2 Flow diagram of training algorithms for MLP network architecture
- Figure 3 Independent and Dependent Variables
- Figure 4 Splitting of Authentic and Counterfeit notes
- Figure 5 Distribution of the data set
- Figure 6 Performance of the ANN mode
- Figure 7 CNN image classification pipeline
- Figure 8 Accuracy and Loss Curves of the CNN model without image augmentation.
- Figure 9 Accuracy and Loss Curves of the CNN model image augmentation

APPENDIX

Appendix A –Python Implementation of Artificial Neural Network

Appendix B – Python Implementation of Convolutional Neural Network

REFERENCES

Chapter 1: Introduction

1.1 Introduction

Image classification has been a hot topic for quite some time. Its overwhelming applications in modern technologies and daily life have been the motivation for continuous research. Now-a-days from social media to medical imaging the applications of image processing are completely evident. A new type of application is also finding its way to become completely integral to our life – that is ensuring security. Bank notes authentication is one of the implementation of this kind of application.

These days, automatic machines accepting banknotes are developed to meet numerous demands and functions. These machines acknowledge banknotes fed to them by finding the design or value of the banknotes. It is extremely essential for such machines to authenticate the banknote to differentiate it between real and counterfeit ones[1]. In general, authentication is more difficult than recognition, because the differences in designs or values are deliberately designed to be readily distinguished, while forgeries are deliberately created for intended purposes to be inseparable from real ones.

To tackle this issue several methods are being used but the technology getting exponentially developed the forgeries are becoming hard to detect. One blessing of the recent colossal growth of computational power has enabled the use of Artificial Intelligence in this situation. Specifically Neural Network can be deployed to detect the counterfeit notes if large amount of training dataset can be provided.

To tackle this issue several methods are being used but the technology getting exponentially developed the forgeries are becoming hard to detect. One blessing of the recent colossal growth of computational power has enabled the use of Artificial Intelligence in this situation. Specifically Neural Network can be deployed to detect the counterfeit notes if large amount of training dataset can be provided [2].

Banknotes are not designed to be used fundamentally with automatic identification purposes. Normally the attributes of the banknotes which are used for identification by those techniques have to be selected on a pragmatic basis. This means, that there is usually no simplified algorithm by which these attributes can be combined to find if the banknotes are authentic or not.

On the other hand, Convolutional Neural Network is basically a modification of the Artificial Neural Network which does not use raw data directly, rather collects the important feature at first and then process it. Convolutional Neural Network can be

effectively used to classify unstructured image data. The convolution layer plays a very crucial part to detect the important features out of the image. Then the max-pooling layer conserves the useful information while reducing the size. The key here is to manipulate the architecture of the network by tweaking between the number and orientation of the convolution layer.

Before the implementation of the proposed network some considerations must be taken including the quality of the images taken and number of it. As these two points play a very important part in achieving the desired accuracy. The convolution Neural Network can be combined with Recurrent Neural Network to add temporal dimension to the spatial one of the convolution stage. Using these two in a combination can give us lots of information which can be used to automate and predict important hidden features [3]. So it can be safely said that the proposed methodologies with this research can be modified accordingly to be used in versatile applications.

1.2 Motivation

With the recent advancement of the computational power, the frontiers of newest technologies are running almost haywire. This computational power growth is often characterized by Moore's Law. Along with this opportunity the Artificial Intelligence has become dominant and is being used in almost every sector. So why not use this chance to solve image classification problems which are very crucial in our modern day sustainability. From the facial recognition in the Facebook to medical imaging in the health sector the image classification is becoming dormant day by day. Due to this present scenario it is essential that the research in image processing must go hand in hand.

On the other hand, forger are becoming more expert too which poses a huge challenge to the authority to ensure security of the bank notes. Traditional techniques often fail because of the sophisticated scanner machines are used to produce counterfeit notes. If we can leverage the current big data analytics along with neural network, it can surely solve this ever growing problem. As abundant of data is available machine can easily learn the difference between real and fake notes [4]. So, from this perspective continuation of novel research in this field is required.

Lastly, Image classification from large unstructured data pose different kinds of challenge where machine need to recognize something given a lot of variation in the input dataset. In this case, the underlying challenge is to implementation of a proper architecture which will facilitate both the result and the accuracy. Moreover, the mega projects from the likes of Google's deep mind are providing the necessary computational packages which can be accessed by the mass people who can easily implement their methods to test if and

validate their results. With that note it is completely evident that the novel research in this exciting field can open new doorways for our future.

1.3 Rationale of the study

Though one can think there are already a bunch of study and techniques are available which can solve a lot of problems, the real consideration is if this will be enough for the future. As I previously said, the technology is getting sophisticated and so do the challenges. Consider a scenario, when a driverless car is going to be populated in all of the major countries, what the risk will come along with it. Proper image recognition is a must to ensure smooth maneuver and security. Those kinds of complex situation demands every bit of research done in advance to be properly handled. As I mentioned the situation is very unique, to solve the most complicated problems the most sophisticated arsenal we have is our brain. So it completely makes sense to develop the newer form of neural network architecture as it the best thing which can mimic the human brain.

Now the main challenges are the formation of some common architectures which can solve the general problems. It is a huge task as the real life scenario can be quite unique and at the same time paradoxical. For example, images can be sometimes hard to distinguish even for human. In order to implement an efficient neural network simultaneous study of the human brain must go hand in hand. At the same time the new findings should be implemented through neural networks to justify and validate those findings.

On the other hand, the existing image processing techniques must be optimized and fine-tuned so that continuous production of the results can be maintained [6]. Specifically, the bank note authentication require lots of study to classify and differentiate the inherent uncertainty. All these things demands that the current research must go on to find the solutions of the newest problems and along with it to enhance the existing technologies. The methods presented here will also need further research as both artificial neural network and convolutional neural network are still in the infant stage. The hyper parameters tuning and a perfect architecture will never become possible unless lots of studies are done.

1.4 Research Questions

This paper focuses on two distinct yet related problems of non-linear image classification. At first, the authentication of bank notes requires few questions to be answered to successfully solve the problem. How the data of the bank notes will be collected gives us few options. Turns out this is the part which defines what kind of neural network should be used for the solution of the problem. In order to process a big amount of data the proper computation platform is needed. Additionally to choose

between the proper libraries to handle the computation can be dwelling too. Whatever the platform or libraries it will require a lot of calculation. How these computation can be done efficiently in terms of time and power is equally important. On the other hand, image classification problem will be implemented through finding the proper classification of cats and dogs from a set of given dataset. This problem is unique in the sense that this dataset is completely unstructured. How to relate between the dependent and independent variables and at the same time with efficacy is the crucial part of the solution. Even with the proper choice among these options, the design of architecture will always need consideration.

Both of the problems require an efficient neural network architecture and flexibility of the computation process. The proper activation functions for both the forward propagation and backward propagation are essential part of designing a neural network. This state normally involves lots of mathematics and statistical methods. Although some pretty useful algorithms are already in existence, the accuracy and efficiency can always get better with the fine-tuning of the hyper parameters and network architecture.

At last from the findings of the results a long term study should be conducted to select between the computation platform, parameters tuning and inherent mathematical methods. Also the connection between the studies may help to bring some new ideas which in turn can be beneficial for the future. The most important questions for both of the problems may be if we should be confined to the existing solution strategies or we should develop some new strategies which can face the ever growing complexities of the image classification.

1.5 Expected Outputs

From the study in this paper, two efficient solutions from the existing technologies will be found. In terms of bank note authentication, the dataset will be made structured from the raw image data. A proper exploratory analysis can reveal the underneath structure among the data itself. Then with a successful implementation of the Artificial Neural Network through python codes and libraries will distinguish between authentic and counterfeit bank notes. The efficiency of the classification will depend on the input dataset. If the dataset contains great amount of noise, it may make some mismatch. Other than that the classification should be pretty impressive as the Artificial Neural Network is very efficient to classify the structured dataset. Though it might give us an excellent result, we should be always careful to cross check our results in case of any discrepancies among the dataset.

On the other hand, the image classification of cats and dogs should give us a good division among the class too if the network is properly trained. The computation should

take long time if GPU based computation is not available for the execution process. Other than that the number of examples can limit the accuracy and loss of our model while performing classification. So with the effective implementation of the algorithm and architecture both of our problems should be efficiently classified.

1.6 Report Layout

This report will first start with the theoretical background of Artificial Neural Network and Convolutional Neural Network and its relevance to this research. Then a brief overview of the current and relevant works will be discussed. After that a comprehensive methodologies will be presented along with detailed description how to perform the task. At first bank note authentication and later image classification of cats and dogs will be addressed. Consequently, the resulting findings will be shown in corresponding graph and a detailed discussions of the results will be presented. In the end, further improvement and potential recommendations will be suggested.

Chapter 2: Background

2.1 Theoretical Background

Artificial neural networks (ANNs) are simply biologically inspired computer programs that are designed to work like the way in which the human brain processes information. ANNs accumulate their knowledge by finding the connections and relationships in the input data and learn through training, not from explicit programming [7]. An ANN is generated from hundreds of single simple units otherwise known as neurons which are connected with corresponding weights and biases that constitute the neural structure and are organized in layers. The power of neural computations derives from the huge connection of neurons in a network. The behavior of a neural network is determined by the activation functions of its neurons, by the learning rule, and by the architecture itself. The weights and biases are the adjustable parameters and, in that sense, a neural network is a parameterized system. The weights and biases are also called as hyper parameter of the neural network because these are not depended on the input data. The weighed sum of the inputs constitutes the activation of the neuron. The activation signal is sent through activation function to produce a single output of the neuron. Activation function incorporates non-linearity to the network with its inherent nature. During training the internal weights and biases are optimized until the error in predictions is reduced to a

acceptable limit. Overall accuracy of the artificial neural network is ensured normally using the back propagation algorithm.

The back-propagation algorithm is a supervised learning method which implements the chain rule of differential calculus. It is particularly useful for feed-forward neural networks. Feed-forward network is the network which has no loop that means it has no feedback opportunity. Back-propagation requires all of the activation functions used by the artificial neurons to be differentiable starting from the network's very last node. Back-propagation is basically deployed to estimate the gradient of error for the network in accordance to its weights and biases. This gradient is fundamentally used in a simple stochastic gradient descent algorithm to match weights that gives minimum error for the network and also to avoid local minima. Stochastic gradient is implemented using a batch learning which means after a batch of inputs are processed, the weights are updated. It is crucial to consider that back-propagation networks are usually multilayer perceptron usually with one input, one hidden, and one output layer but there are exceptions too.




Figure 1: Architecture of Artificial Network

After the network has been trained and tested it can be provide with the new input information to predict the output. Varieties of neural networks have been designed in the last couple of decades and novel ones are invented every now and then but all can be described by the activation functions of their neurons, by the learning rule, and by the connection formula. ANN constitutes an optimistic modeling strategy, especially for data sets having non-linear relationships which are commonly encountered in world-wide-web and pharmaceutical processes. To specify the model, artificial neural networks require no additional information of the data source but, because they normally hold many weights and biases which must be calculated, they need very large training datasets. Additionally, ANNs can fuse and interconnect both empirical and literature-based data to solve

different kinds of problems. The numerous applications of ANNs can be abstracted into prediction, pattern recognition or classification and modeling. Supervised learning networks can be used in medical and business fields to supplement the existing technologies. Unsupervised networks gives us a new way in addition to principal component analysis. Non-adaptive unsupervised networks are capable to reorient the patterns when provided with noisy samples and can be implemented for image classification.




Figure 2: Flow diagram of training algorithms for MLP network architecture

On the other hand, Convolutional Neural Networks are deep artificial neural networks that are used primarily to classify images, cluster them by finding commonalities and perform object recognition [8]. They are the algorithms and architectures which can differentiate individual faces, street signs, tumors, platypuses and many other aspects of visual data. Convolutional neural network has a built-in facility to incorporate additional convolutional layers which collects important features while reducing a great amount of size. These architecture can be greatly manipulated to increase the accuracy.

The superior performance of convolutional network in image classification is one of the most prominent reasons why the recent trend is picking overwhelming use of it. This is the main driving force in computer vision which in turn the key factor to successfully

implement self-driving cars, robotics, drones, security, medical diagnoses, and treatments for the visually impaired. The interesting fact is that it start from a very simple image classification to very complicated pattern detection. Though there are some difficulties while using convolutional neural network.

The working principle of Convolutional Neural Network can described in following ways. At first input vector of images are put into convolution layer. There are numerous feature detectors which grabs the specific features from the input data and thereby reducing the size of the image. In the next step, convoluted features are passed through the max-pooling layers which just grabs the most important features of the convoluted data. Here the size of the images are significantly reduced but the features are not lost because from every max-pooling filter the most important features are conserved. Thus it ensures if the test image comes in different orientation it can still detect the inherent features. After the max-pooling layer dataset are flattened into a long single vector which is the input of the adjacent Artificial Neural Network. One thing to note here that the hidden layers of this type of network is fully connected thereby it is also called fully connected layer. The main benefit here the input of the ANN is already a refined vector which maximize the efficiency.




Figure 3: CNN image classification pipeline

2.2 Related Works

Artificial Intelligence particularly Simple Perceptron was first developed in 1957 at the Cornell Aeronautical Laboratory by Frank Rosenblatt. Rosenblatt showed how a binary classification problem can be automated with the use of simple perceptron. Since then lots of research have been conducted in the field of artificial intelligence. Neural Network

became very popular in 1980's when the renowned godfather of neural network Geoffrey Hinton found some breakthroughs. Along with him some other researchers made some remarkable contributions but the idea while envisioned at first slowly died off in the 1990's. As neural network need large dataset to train the input data to maximize the result, the technology at that time did not permit the large scale implementation of neural network. But as the recent growth in the computational power, the idea of neural network has been revitalized and has created difference in a very short span of time.

However, the latest research is on mostly combining multiple neural network framework to create a hybrid platform that can perform complex tasks which otherwise seems impossible. Google's deep mind is one of the sophisticated example of this kind of hybrid network which can automatically identify a person's face and tag them. Especially combining convolutional layer with recurrent layer gives a huge boost because recurrent layer adds temporal dimension in addition to convolutional layer's spatial dimension. Some of the examples are – making movie subtitles, describing an image completely which means what is the image and what is going on in that image too. Even this hybrid network can be used to develop precision medicine and genome sequencing. Last but not the least, if we want to implement full scale driverless cars in our road, we need to find a complete efficient hybrid network of convolutional and recurrent layers.

2.3 Research Summary

The main purpose of this research is to implement two types of neural network which is Artificial Neural Network and Convolutional Neural Network and while doing so effectively classify image data mainly. After the successful implementation some challenges and inherent scope for improvement are found. To address these issues while the research is being done and also keeping those for the future works is crucial. Especially the profound complexity associated with the fine-tuning of neural network and tackling these challenges to get excellent results are the outcomes of this research.

2.4 Scope of the Problem

Both of our problems are very simplistic in nature, at least considering how much complexity a neural network can contain. So the main target is to classify structured image data in Artificial Neural Network and unstructured image data in Convolutional Neural network. After that analyzing the results from the corresponding graphs and numerical results are also considered with equal importance. In addition, what tweaks and tricks can be used to make the networks more efficient and effective and also getting expected results after analyzing those aspects are addressed. However, developing new algorithms or mathematical equations and conducting novel experiments are not in the scope of this research.

2.5 Challenges

The main challenges associated with the research are as follows-

- ✓ Getting good quality datasets with needed attributes.
- ✓ Preprocessing of the datasets for the effective analysis.
- ✓ Corresponding exploratory data analysis to visualize the nature of the datasets.
- ✓ Choosing a proper programming platform and corresponding libraries.
- ✓ Incorporating GPU computing along with CPU computing to reduce time complexity.
- ✓ Choosing proper initial hyper parameters and tweaking them while programming.
- ✓ Finding the optimal number of convolutional layers in CNN implementation.
- ✓ Getting enough data to train the neural network properly.
- ✓ To choose the correct activation functions in both hidden and output layers.
- ✓ To avoid over fitting in Convolutional Neural Network.

Chapter 3: Research Methodologies

3.1 Introduction

The research of this paper will follow an organized strategy to solve two non-linear classification problems. At first two datasets for two problems will be collected from two different sources. Preprocessing will be done for the authentication of bank notes and will not be required for the image classification of cats and dogs. Preprocessing is conducted for the standardization of the input datasets. Data exploration will be done for Artificial Neural Network afterwards for the first problem. Then the networks will be initialized and datasets will be split accordingly. Consequently, the training of the networks will be done with the given training data. Then the right class of the test datasets will be predicted with the test data. For Convolutional Neural Network some additional steps will be required. First of all, image augmentation will be needed to avoid over fitting and

then on top of Artificial Neural Network there will be corresponding initialization of the convolutional layer, max-pooling layer and flattening layer. After that Classifier objects will be run to get the results and analyze them in respective graphs to find the overall scenario and pitfalls.

The detailed explanation of bank note authentication is as follows-

3.1.1. Image Acquiring

Images can be taken with high quality camera or scanner. All of the features of the images should be conserved. In case of ensuring the quality industrial camera may be used.

3.1.2. Gray Scale Transformation

Image stored in the previous step is too large to process. Additionally, color information is not needed though the indices of the colors are. Then RGB image is converted into their corresponding pixel values and then gray scale image is transformed with 660 dpi.

3.1.3 Wavelet Conversion

It is the basic requirement in image processing. Wavelet Transform tool are utilized to extract attributes from images [9]. The data feature information:

- ✓ Variance of Wavelet Transformed image (continuous)
- ✓ Skewness of Wavelet Transformed image (continuous)
- ✓ Kurtosis of Wavelet Transformed image (continuous)
- ✓ Entropy of image (continuous)
- ✓ Class (integer)

3.1.4. Image Partition

In this step images are segmented in accordance with their properties and nature. For example, Monochromatic images will be partitioned according to intensity and shape.

3.1.5. Output

Outputs are meticulously analyzed to find the failed cases to measure the networks accuracy so that it can be used in the future to design the algorithm and select the model more accurately.

3.2 Research Subject and Instrumentation

The research subject is basically non-linear image classification. This research will be conducted with two neural networks – Artificial Neural Network and Convolutional Neural Network and two data sets. One from UCI Machine Learning repository and the other is from Kaggle datasets. The overall process involves collecting, analyzing and presentation of the results obtained from neural network implementation of two different kinds.

3.3 Data Collection Procedure

Bank note dataset has been collected from taking images thousands of real bank notes. From the raw data of the image four features will be selected to make a structured data frame. Though the structured data have been taken from UCI machine learning repository which is open source but the requirement is that whoever takes this data for research purpose has to give proper citation [10]. The bank note dataset selected for this research contains 1372 instances. On the other hand, the dataset for cats and dogs image classification has been collected from Kaggle machine learning dataset which is also open source but the citation credit has to be given. It contains 25000 images of cats and dogs but in this experiment to reduce the computation time 8000 are selected. To be able to connect independent variables which are just numerical values in this case with the dependent variable which is the classes of cats and dogs two distinct folders are created in working directory labeling the classes properly. So in this paper both of the required datasets are collected from open source platforms.

3.4 Statistical Analysis

The collected data should be statistically fit to process in the neural network. Normally the data is made standardized so that the numerical value fit into a closer range. The data should also be uniform or normally distributed some of the time to get desired results. In this case, the data is already statistically processed so no addition steps had to be done.

3.5 Implementation Requirements

The research subjects of this paper are datasets of bank note from UCI machine learning repository and images of cats and dogs from Kaggle. The programming platform needed to analyze the data is Python and its deep learning libraries – Tensorflow, Contrib.Learn and Keras. Additionally for exploration Matplotlib and Seaborn will be used. To perform efficient and avoid time complexity GPU enabled computing system will be needed.

Chapter 4: Experimental Results and Discussions

4.1 Introduction

The accuracy of the bank note authentication is very accurate. It classifies all of the data correctly while the accuracy level of the image classification of cats and dogs is nearly 80%. Also the data of the bank note authentication is almost separable that is the reason for excellent accuracy. On the other hand, image classification in the second experiment is much more complex. Due to added convolution layer and the size of the data the computation time is much larger. However, the results are quite satisfactory but still leaves room for improvements.

4.2 Experimental Results

The results found after performing the computation of the bank notes are as follows-

	Image.Var	Image.Skew	Image.Curt	Entropy	Class
0	3.62160	8.6661	-2.8073	-0.44699	0
1	4.54590	8.1674	-2.4586	-1.46210	0
2	3.86600	-2.6383	1.9242	0.10645	0
3	3.45660	9.5228	-4.0112	-3.59440	0
4	0.32924	-4.4552	4.5718	-0.98880	0

Figure 4: Independent and Dependent Variables




Figure 5: Splitting of Authentic (0) and Counterfeit (1) notes




Figure 6: Distribution of the data set




Figure 7: Performance of the ANN model

Confusion Matrix:

```
[[237   0]
 [ 1  174]]
```

Performance Metrics

	precision	recall	f1-score	support
0	1.00	1.00	1.00	237
1	1.00	0.99	1.00	175
avg / total	1.00	1.00	1.00	412

The results from the cats and dogs image classification are as follows-



Figure 8: Accuracy and Loss Curves of the CNN model without image augmentation.




Figure 9: Accuracy and Loss Curves of the CNN model with image augmentation.

4.3 Descriptive Analysis

From figure 4 it is evident that the range of the values in the bank note dataset is very close. So it does not require standard scaling. However to be in the safe side this experiment considers standardizing the dataset. While figure 5 represents the count plot of the dataset. From the corresponding count plot we can see that almost 760 of the total 1372 instances are authentic notes and the rest are counterfeit. Then figure 6 gives us the pair plot of the dataset. From this figure it is evident that the independent variables are quite separable from each other. However, there are some overlaps in curtosis and entropy regions. This conspicuous separation yields to a very good results. After that standard scalar function is used to standardize the data. Then a set of 70% training data and 30% test data is split. After that in Tensorflow a classifier object is created. Using step size of 200 and batch size of 20 the training data is made fit into the model. Now model evaluation is done to predict the result and the results are shown in the corresponding classification report and confusion matrix. Figure 7 shows the cost function over time. It is seen that the cost function quickly reduces to a minimum value and become stable. With this finding we can conclude that our model was a good selection for Artificial Neural Network for bank note classification. Now from confusion matrix the supremacy of the model is complexly obvious as it classifies all of the real notes correctly just one wrong prediction in the counterfeit note which is acceptable. From the performance matrix the accuracy of the model is known and we can see that the test set was of size 412 and it identifies all 237 real notes correctly and 174 out of 175 counterfeits correctly.

Now the performance of the Convolutional Neural Network will be discussed from figure 8 and 9 which are generated with the help of matplotlib library. Our CNN model cannot outperform the ANN model in this case because ANN models had fewer and structured data while CNN had 8000 of instances which are also totally unstructured. Nonetheless, the result is quite satisfactory for CNN with a accuracy of 80%. Though this accuracy was obtained using additional convolutional and max-pooling layer. But from last two figure an interesting phenomena is noticed. In figure 8 both the loss and the accuracy in the test set cannot match the training results. It somehow reduces for the loss function and increases in the accuracy function nevertheless shows a constant fluctuation. This is because of the over fitting caused by the lower number of instances in the training set. What happens is that the machine memorizes the training data very well due to lower in number and that's why it cannot generalize the pattern. Ultimately when an unknown test set is given it cannot classify properly. On the other hand, in figure 9 the test set matches the training set both in terms of loss and accuracy. The reason is in first case image augmentation was not used while in the second case it was used. Image augmentation is the process where the images in the training set is randomly transformed linearly to create

multiple instances within the training set. This enables us to increase the number of examples which helps the machine to learn properly.

4.4 Summary

Both of the neural networks perform quite well and effectively find the solutions for our non-linear classification problems. Still there are rooms for improvements by tweaking some parameters and hyper parameters of the networks. The computation time for the Convolutional Neural Network is a big issue if GPU computing is not used. Fortunately in our case the availability of GPU computing enabled us to choose a bigger epoch size and thereby making the learning process easier and accurate for the networks. In bank note authentication 411 instances out of 412 were successfully classified and in the cats and dogs image classification almost 80% of the time the network was correct in guessing the right class.

Chapter 5: Conclusion, Recommendation and Implication for the future

5.1 Conclusion

This thesis paper was particularly divided into two different problems for Artificial Neural Network and Convolutional Neural Network. The proposed methodologies successfully generated the desired results with some interesting observations. These observations intrigued a myriad of recommendations and scope of future study regarding neural network as a whole.

5.2 Recommendations

For bank note authentication –

- ✓ Experiment on the initialization of weights and biases in the network
- ✓ Splitting training and test data properly and standardization of the dataset.

For image classification of cats and dogs-

- ✓ Using deeper Convolutional Neural Network.
- ✓ In some cases adding additional fully connected layers.

- ✓ Adding extra feature detectors in the subsequent convolutional layers.

5.3 Implication for Further Study

The revitalization of the neural network has been a true hope for an intelligent future. The limited resources we have cannot ensure the sustainability of our future. Proper implementation and research of Neural Networks can help us fully deploy intelligent machine to work on our behalf. With this note two of the supervised neural network model has been the subjects of our study but lots of other variants of the networks still deserves proper and in depth research. The manipulation of the mathematical models and algorithms can give birth to new types of networks. Especially, combining convolutional and recurrent neural network is the next big thing which can solve some of the complicated real life problems. Also an meticulous look at the reinforcement learning is of no lesser importance.

Appendix

Appendix A: ANN Python Implementation

```
# Using pandas to read in the bank_note_data.csv file

import pandas as pd

data = pd.read_csv('bank_note_data.csv')

#Checking the head of the Data

data.head()

#Import seaborn and set matplotlib inline for viewing

import seaborn as sns %matplotlib inline

#Creating a Countplot of the Classes (Authentic 1 vs Fake 0)

sns.countplot(x='Class',data=data)

#Creating a PairPlot of the Data with Seaborn, set Hue to Class

sns.pairplot(data,hue='Class')
```

```

#Standard Scaling

from sklearn.preprocessing import StandardScaler

#Create a StandardScaler() object called scaler.

scaler = StandardScaler()

#Fitting scaler to the features.

scaler.fit(data.drop('Class',axis=1))

StandardScaler(copy=True, with_mean=True, with_std=True)

#Use the .transform() method to transform the features to a scaled version.

scaled_features = scaler.fit_transform(data.drop('Class',axis=1))

#Convert the scaled features to a dataframe and check the head of this dataframe to make
sure the scaling worked.

df_feat = pd.DataFrame(scaled_features,columns=data.columns[:-1])

df_feat.head()

#Train Test Split

Create two objects X and y which are the scaled feature values and labels respectively.

X = df_feat

y = data['Class']

#Using the .as_matrix() method on X and Y and reset them equal to this result. We need
to do this in order for TensorFlow to accept the data in Numpy array form instead of a
pandas series.

X = X.as_matrix()

y = y.as_matrix()

#Using SciKit Learn to create training and testing sets of the data:

from sklearn.cross_validation import train_test_split

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3)

#Importing Contrib.learn

```

```
Import tensorflow.contrib.learn.python.learn as learn
```

```
import tensorflow.contrib.learn.python.learn as learn
```

Create an object called classifier which is a DNNClassifier from learn. Setting it to have 2 classes and a [10,20,10] hidden unit layer structure:

```
classifier = learn.DNNClassifier(hidden_units=[10, 20, 10], n_classes=2)
```

#Now fitting classifier to the training data. Use steps=200 with a batch_size of 20.

```
classifier.fit(X_train, y_train, steps=200, batch_size=20)
```

```
/Users/marci/anaconda/lib/python3.5/site-
```

```
packages/tensorflow/python/ops/array_ops.py:1197: VisibleDeprecationWarning:  
converting an array with ndim > 0 to an index will result in an error in the future
```

```
result_shape.insert(dim, 1)
```

```
DNNClassifier()
```

#Model Evaluation

Using the predict method from the classifier model to create predictions from X_test

```
note_predictions = classifier.predict(X_test)
```

Now creating a classification report and a Confusion Matrix.

```
from sklearn.metrics import classification_report, confusion_matrix
```

```
print(confusion_matrix(y_test, note_predictions))
```

```
print(classification_report(y_test, note_predictions))
```

Appendix B: CNN Python Implementation

```
from keras.models import Sequential
```

```
from keras.layers import Convolution2D
```

```
from keras.layers import MaxPooling2D
```

```
from keras.layers import Flatten
```

```

from keras.layers import Dense

#initializing the CNN

classifier = Sequential()

#Convolution

classifier.add(Convolution2D(32,kernel_size=(3,3),input_shape=(64,64,3),data_format="
channels_last",activation = 'relu'))

#MaxPooling

classifier.add(MaxPooling2D(pool_size=(2,2)))

#Flattening

classifier.add(Flatten())

#Full Connection

classifier.add(Dense(units=128,activation='relu'))

classifier.add(Dense(units=1,activation='sigmoid'))

#Compiling the CNN

classifier.compile(optimizer='adam',loss = 'binary_crossentropy',metrics=['accuracy'])

#Fitting the CNN to the image

from keras.preprocessing.image import ImageDataGenerator

train_datagen = ImageDataGenerator(

    rescale=1./255,

    shear_range=0.2,

    zoom_range=0.2,

    horizontal_flip=True)

test_datagen = ImageDataGenerator(rescale=1./255)

training_set = train_datagen.flow_from_directory(

    'dataset/training_set',

```

```
target_size=(64, 64),
batch_size=32,
class_mode='binary')
test_set = test_datagen.flow_from_directory(
    'dataset/test_set',
    target_size=(64, 64),
    batch_size=32,
    class_mode='binary')
classifier.fit_generator(
    training_set,
    steps_per_epoch=8000,
    epochs=20
    validation_data=test_set,
    validation_steps=2000)
```

Reference

- [1] Roy, Ankush, Biswajit Halder, and Utpal Garain. "Authentication of currency notes through printing technique verification." *Proceedings of the Seventh Indian Conference on Computer Vision, Graphics and Image Processing*. ACM, 2010.
- [2] Mohamad, Nur Syuhada, et al. *Banknote authentication using artificial neural network*. Diss. Universiti Teknikal Malaysia Melaka, 2015.
- [3] Krizhevsky, Alex, Ilya Sutskever, and Geoffrey E. Hinton. "Imagenet classification with deep convolutional neural networks." *Advances in neural information processing systems*. 2012.
- [3] Agasti, Tushar, et al. "Fake currency detection using image processing." *IOP Conference Series: Materials Science and Engineering*. Vol. 263. No. 5. IOP Publishing, 2017.
- [4] Bhaskar, Jonathan, and Ankit Patel. "Image Classification using Convolutional Neural Network."
- [5] Prime, Emma L., and David H. Solomon. "Australia's plastic banknotes: fighting counterfeit currency." *Angewandte Chemie International Edition* 49.22 (2010): 3726-3736.
- [6] Singh, Yashpal, and Alok Singh Chauhan. "NEURAL NETWORKS IN DATA MINING." *Journal of Theoretical & Applied Information Technology* 5.1 (2009).
- [7] Hempel, Arne-Jens, et al. "SVM-integrated fuzzy pattern classification for nonconvex data-inherent structures applied to banknote authentication." *Bildverarbeitung in der Automation. inIT, Lemgo* (2012).
- [8] Liu, Jiongxin, et al. "Dog breed classification using part localization." *European Conference on Computer Vision*. Springer, Berlin, Heidelberg, 2012.
- [9] Xiao, Tianjun, et al. "The application of two-level attention models in deep convolutional neural network for fine-grained image classification." *Computer Vision and Pattern Recognition (CVPR), 2015 IEEE Conference on*. IEEE, 2015.
- [10] Frank, R. "The perceptron a perceiving and recognizing automaton." *Cornell Aeronautical Laboratory, Buffalo, NY, USA, Tech. Rep* (1957): 85-460.