

# **RNN-Based Weather Forecast Prediction: A Modern Approach**

**By**

**Mahmudur Rahman**

**ID: 201-15-3670**

## **FINAL YEAR DESIGN PROJECT REPORT**

This Report Presented in Partial Fulfillment of the  
Requirements for the **Degree of Bachelor of Science in  
Computer Science and Engineering**

**Supervised by**

**Mr. Mahimul Islam Nadim**

**Lecturer**

Department of Computer Science and Engineering  
Daffodil International University

**Co-Supervised by**

**Mr. Md Assaduzzaman**

**Senior Lecturer**

Department of Computer Science and  
Engineering Daffodil International University



**DAFFODIL INTERNATIONAL  
UNIVERSITY  
Dhaka, Bangladesh**


**January 13, 2025**

# APPROVAL

---

This Project titled “RNN-Based Weather Forecast Prediction: A Modern Approach,” submitted by **Md. Mahmudur Rahman** to the Department of Computer Science and Engineering, Daffodil International University, has been accepted as satisfactory for the partial fulfillment of the requirements for the degree of B.Sc. in Computer Science and Engineering and approved as to its style and contents. The presentation has been held on **13-01-2025**.

## BOARD OF EXAMINERS

  
13/1/25

**Dr. Md. Taimur Ahad (MTA)**

**Board Chairman**


Associate Professor & Associate  
Head, Department of CSE, FSIT  
Daffodil International  
University

  
13/1/25

**Mohammad Monirul Islam (MMI)**

**Internal Examiner 1**

Assistant Professor, Department  
of CSE, FSIT Daffodil  
International University

  
13/01/25

**Md. Jakaria Zobair (MJZ)**

**Internal Examiner 2**

Lecturer, Department of CSE,  
FSIT Daffodil International  
University

  
13/01/2025

**Nazibur Rahman**

**External Examiner**


Technical Lead Database Administrator  
Telenor · Grameen Phone Account

# DECLARATION

---

We hereby declare that this project has been done by us under the supervision of **Mr. Mahimul Islam Nadim**, Lecturer, Department of Computer Science and Engineering, Daffodil International University. We also declare that neither this project nor any part of this project has been submitted elsewhere for the award of any degree or diploma.

Supervised by:

  
28/11/24

---

**Mr. Mahimul Islam Nadim**

Lecturer

Department of Computer Science and  
Engineering Daffodil International  
University

Co-Supervised by:

---

**Mr. Md Assaduzzaman**

Lecturer

Department of Computer Science and  
Engineering Daffodil International  
University

Submitted by:



---

**Mahmudur Rahman**

ID: 201-15-3670

Department of Computer Science and  
Engineering Daffodil International  
University

# ACKNOWLEDGEMENTS

---

This work would not have been possible without the support and contributions of many individuals over the past two semesters. We are deeply grateful to everyone who has assisted us in one way or another.

First, we express our heartfelt thanks and gratefulness to the almighty for His divine blessing making it possible for us to complete the **Final Year Design Project (FYDP)** successfully.

We are grateful and wish our profound indebtedness to **Mr. Mahimul Islam Nadim, Lecturer**, Department of Computer Science and Engineering, Daffodil International University, Dhaka, Bangladesh. Deep knowledge and keen interest of our supervisor in the field of **Machine learning** to carry out this project. His endless patience, scholarly guidance, continual encouragement, constant and energetic supervision, constructive criticism, valuable advice, reading many inferior drafts, and correcting them at all stages have made it possible to complete this project.

We would like to express our heartfelt gratitude to the **Head of the Department of Computer Science and Engineering**, for his kind help in finishing our project and also to other faculty members and the staff of the Department of Computer Science and Engineering, Daffodil International University.

We would like to thank our entire course-mates at Daffodil International University, who took part in this discussion while completing the coursework.

Finally, we must acknowledge with due respect the constant support and patience of our parents.

# ABSTRACT

Accurate weather forecasting is vital for resource planning, disaster management, and informed decision-making. This study leverages deep learning techniques, including Long Short-Term Memory (LSTM), Gated Recurrent Units (GRU), and 1D Convolutional Neural Networks (1D CNN), to predict weather trends from sequential data. Extensive preprocessing was conducted to ensure data integrity and compatibility with the models. Among the evaluated models, the 1D CNN and LSTM demonstrated superior performance, achieving regression accuracies of 83.09% and 83.44%, respectively. The GRU model also performed reliably, with a regression accuracy of 81.72%. A Hybrid CNN-LSTM model was tested but exhibited significantly lower performance, highlighting the robustness of standalone LSTM and CNN models for weather prediction tasks. Future work will focus on incorporating larger datasets, enhancing interpretability through explainable AI, and exploring more advanced architectures. This research underscores the effectiveness of deep learning models for time-series forecasting and provides valuable insights into their comparative performance

# Table of Contents

<b>Approval</b>	<b>i</b>
<b>Declaration</b>	<b>ii</b>
<b>Acknowledgements</b>	<b>iii</b>
<b>Abstract</b>	<b>iv</b>
<b>List of Figures</b>	<b>vii</b>
<b>List of Tables</b>	<b>viii</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Introduction.....	1
1.2 Motivation.....	1
1.3 Objectives.....	2
1.4 Methodology.....	3
1.5 Project Outcome.....	4
1.6 Organization of the Report.....	4
<b>2 Background</b>	<b>6</b>
2.1 Introduction.....	6
2.2 Literature Review.....	6
2.2.1 Similar Applications.....	6
2.2.2 Related Research.....	6
2.3 Gap Analysis.....	8
2.4 Summary.....	8
<b>3 Research Methodology</b>	<b>9</b>
3.1 Methodology/Requirement Analysis & Design Specification.....	9
3.1.1 Overview.....	9
3.1.2 Proposed Methodology/ System Design.....	9
3.1.3 Functional and Nonfunctional Requirements.....	9
3.1.4 Context Diagram.....	9
3.1.5 Data Flow Diagram Level 1.....	9

3.1.6	UI Design .....	9
3.2	Detailed Methodology and Design .....	10
3.3	Project Plan.....	15
3.4	Task Allocation .....	16
3.5	Summary.....	17
<b>4</b>	<b>Implementation and Results</b>	<b>18</b>
4.1	Environment Setup .....	18
4.2	Testing and Evaluation/Performance/ Comparative Analysis.....	18
4.3	Results and Discussion .....	28
4.4	Summary.....	31
<b>5</b>	<b>Engineering Standards and Design Challenges</b>	<b>32</b>
5.1	Compliance with the Standards .....	32
5.1.1	Software Standards.....	32
5.1.2	Hardware Standards.....	32
5.1.3	Communication Standards.....	33
5.2	Impact on Society, Environment and Sustainability.....	33
5.2.1	Impact on Life .....	33
5.2.2	Impact on Society & Environment .....	34
5.2.3	Ethical Aspects.....	34
5.2.4	Sustainability Plan .....	34
5.3	Project Management and Financial Analysis.....	35
5.4	Complex Engineering Problem .....	36
5.4.1	Complex Problem Solving.....	36
5.4.2	Engineering Activities.....	38
5.5	Summary.....	40
<b>6</b>	<b>Conclusion</b>	<b>41</b>
6.1	Summary.....	41
6.2	Limitation .....	41
6.3	Future Work.....	42
	<b>References</b>	<b>43</b>

# List of Figures

3.1 Model architecture.....	9
3.2 Max and min temp .....	11
3.3 Precipitation over time.....	11
3.4 Wind speed over time .....	12
3.5 Weather condition frequency.....	12
4.1 Training and validation loss curve (LSTM).....	20
4.2 Residuals vs Predicted Values(LSTM).....	20
4.3 Actual vs Predicted Values(LSTM) .....	21
4.4 Distribution of actual vs predicted values(LSTM).....	21
4.5 Training and validation loss curve(GRU).....	22
4.6 Residuals vs predicted values(GRU).....	22
4.7 Actual vs predicted values(GRU) .....	23
4.8 Distribution of actual vs predicted values(GRU) .....	23
4.9 Training and validation loss curve(1D) .....	24
4.10 Residuals vs predicted values(1D).....	24
4.11 Actual vs predicted values(1D).....	25
4.12 Distribution of actual vs predicted values(1D).....	25
4.13 Training vs validation loss curve(HCL) .....	26
4.14 Residuals vs predicted values(HCL).....	26
4.15 Actual vs predicted values(HCL).....	27

# List of Figures

4.16 Distribution of actual vs predicted values(HCL).....	27
4.17 Actual vs Predicted Values Comparison for All Models.....	29
4.18 Residuals Distribution Comparison for All Models.....	29
4.19 Training and validation Loss Curve For All Models.....	30
4.20 Regression Accuracy Comparison .....	30
4.21 MSE Comparison .....	31

# List of Tables

2.1 Summary Of Literature Review.....	6
3.1 Project Plan .....	15
3.2 Task Allocation .....	16
4.1 Comparative Model Table.....	29
5.1 Financial Analysis.....	35
5.2 Mapping with complex problem solving.....	36
5.3 Mapping with knowledge profile.....	37
5.4 Mapping with Complex Engineering Activities .....	39

# Chapter 1

## Introduction

This chapter introduces the research on weather forecasting using advanced deep learning techniques. It discusses the background of the problem, the motivation for the study, the objectives, the methodology adopted, the expected outcomes, and the structure of this report.

### 1.1 Introduction

Accurate weather forecasting plays a vital role in various sectors, including agriculture, disaster management, transportation, and energy planning. However, predicting weather conditions accurately is a challenging task due to the dynamic and non-linear nature of weather patterns. This research explores the use of advanced machine learning techniques, particularly Recurrent Neural Networks (RNN), for weather prediction.

The study focuses on implementing and comparing multiple deep learning models, including Long Short-Term Memory (LSTM), Gated Recurrent Units (GRU), and 1D Convolutional Neural Networks (1D CNN). These models are specifically designed to handle sequential data, making them well-suited for time-series forecasting tasks. A hybrid CNN-LSTM model was also tested to explore its potential for combining spatial and temporal feature extraction.

The dataset used for this study comprises weather parameters recorded over time, and extensive preprocessing was carried out to ensure data integrity. A sliding window approach was utilized to prepare the data for input into the models, capturing relevant temporal dependencies. Each model was trained and evaluated to determine its performance in predicting future weather conditions.

Through rigorous evaluation, the LSTM and 1D CNN models demonstrated the best performance, achieving regression accuracies of 83.44% and 83.09%, respectively. The GRU model performed reliably with an accuracy of 81.72%. The hybrid CNN-LSTM model, while tested, exhibited lower performance, highlighting the strength of standalone models for this specific task.

This research highlights the potential of deep learning for weather prediction and provides a comprehensive comparison of different architectures for analyzing sequential data. By leveraging these models, more accurate and reliable weather forecasts can be generated, benefiting critical decision-making processes across various domains. The following sections will discuss the methodology, results, and implications of this study in detail.

## 1.2 Motivation

The motivation behind this research lies in the critical importance of accurate weather forecasting in various fields and the challenges associated with traditional prediction methods. Weather plays a fundamental role in agriculture, energy management, disaster preparedness, and transportation. Timely and reliable forecasts can mitigate risks, improve planning, and prevent significant economic losses.

Traditional forecasting methods rely heavily on statistical models and numerical weather prediction (NWP) systems, which are computationally expensive and often struggle to handle the non-linear and chaotic nature of weather patterns. With the advent of machine learning and deep learning, a new avenue has emerged for developing more efficient and accurate forecasting techniques that can effectively analyze vast amounts of sequential weather data.

Recurrent Neural Networks (RNN), along with specialized variants such as Long Short-Term Memory (LSTM) and Gated Recurrent Units (GRU), have demonstrated exceptional performance in capturing temporal dependencies in time-series data. Similarly, Convolutional Neural Networks (CNN) have shown their effectiveness in extracting spatial patterns, making them highly suitable for weather-related predictions.

The primary motivation of this study is to explore how these advanced machine learning models can be utilized to improve the accuracy of weather forecasts. By comparing the performance of LSTM, GRU, and 1D CNN models, as well as testing a hybrid CNN-LSTM architecture, this research aims to identify the most effective approach for weather prediction.

Moreover, understanding the limitations of hybrid models and highlighting the strengths of individual architectures will provide valuable insights for future research in this domain. This study seeks to contribute to the growing body of knowledge in machine learning-based weather forecasting and inspire the development of innovative solutions for real-world challenges in meteorology.

## 1.3 Objectives

The primary objectives of this research are as follows:

### **Data Collection:**

Utilize a comprehensive dataset containing historical weather data, including key meteorological parameters such as temperature, humidity, and other relevant features.

Ensure the dataset is complete, reliable, and suitable for time-series forecasting tasks.

### **Data Preprocessing :**

Perform thorough preprocessing to handle missing values, remove duplicates, and normalize the dataset for efficient model training.

Implement a sliding window approach to transform the sequential data into training and testing sets, capturing the temporal dependencies effectively.

**Model Development :**

Develop and implement advanced machine learning models, including Long Short- Term Memory (LSTM), Gated Recurrent Units (GRU), and 1D Convolutional Neural Networks (1D CNN), for weather prediction.

Experiment with a hybrid CNN-LSTM model to explore its capability in integrating spatial and temporal feature extraction.

**Model Evaluation :**

Evaluate the performance of each model using metrics such as Mean Squared Error (MSE), Mean Absolute Error (MAE), R-squared ( $R^2$ ), and Regression Accuracy.

Identify the best-performing model based on the evaluation results and analyze its predictions.

**Comparison and Analysis :**

Conduct a comparative analysis of all implemented models to determine their strengths, weaknesses, and suitability for weather forecasting tasks.

Highlight the limitations of the hybrid CNN-LSTM model and discuss the advantages of simpler architectures for specific tasks.

**Result Visualization :**

Visualize key insights using plots for training and validation losses, residual analysis, and the distribution of actual vs. predicted values.

Provide intuitive and clear visualizations to support the interpretation of model performance.

**Conclusion and Recommendations :**

Draw conclusions based on the findings of this study and provide recommendations for future work in deep learning-based weather forecasting.

Suggest potential improvements and alternative approaches for enhancing prediction accuracy and efficiency.

## 1.4 Methodology

**Data Preprocessing :**

The weather dataset underwent several preprocessing steps to prepare it for predictive modeling.

Missing values were identified and handled using imputation techniques to ensure data completeness. Duplicate entries were removed to maintain the dataset's integrity. To standardize the data, feature normalization was applied, ensuring all variables were scaled to a common range. A sliding window approach was implemented to segment sequential weather data into overlapping sequences, enabling the preservation of temporal dependencies crucial for time-series analysis.

**Model Development :**

The project employed multiple machine learning architectures to identify the most effective model for weather forecasting. LSTM models were implemented to capture long- term dependencies in the time-series data. GRU models, known for their computational

efficiency, were used to model temporal relationships effectively. A 1D CNN model was developed to extract local patterns from sequential data, leveraging its strength in identifying spatial features. Additionally, a hybrid CNN-LSTM model was designed to combine CNNs for feature extraction and LSTMs for sequence modeling. However, the hybrid model demonstrated lower accuracy than the other models, highlighting its limited applicability in this context.

#### **Evaluation and Optimization :**

The models were evaluated using metrics such as Mean Squared Error (MSE), Mean Absolute Error (MAE), R-squared ( $R^2$ ), and Regression Accuracy. These metrics provided a comprehensive view of the models' predictive capabilities. Hyperparameter tuning was conducted to optimize learning rates, the number of layers, and dropout rates, improving model performance. Early stopping techniques were applied during training to avoid overfitting and preserve the best-performing model. Comparative analysis revealed that the LSTM and 1D CNN models performed the best, achieving regression accuracies of 83.44% and 83.09%, respectively, while the GRU model achieved 81.72% accuracy.

#### **Result Analysis :**

To evaluate the performance and reliability of the models, several visualization techniques were employed. Training and validation loss curves illustrated the learning progression of the models, while graphs comparing actual and predicted values showcased the accuracy of predictions. Residual plots were used to analyze the distribution of errors, and the distribution of actual versus predicted values highlighted the models' ability to approximate the real data distribution. The analysis confirmed the effectiveness of LSTM and 1D CNN models in weather forecasting, with the hybrid model demonstrating limited success in capturing temporal and spatial dependencies.

## **1.5 Project Outcome**

1. Development of an automated weather forecasting system utilizing advanced deep learning techniques for sequential data analysis.
2. Identification of LSTM and 1D CNN models as the most effective frameworks, achieving regression accuracies of 83.44% and 83.09%, respectively.
3. Implementation of multiple architectures, including GRU and Hybrid CNN- LSTM, providing insights into the strengths and limitations of different models in time-series forecasting.
4. Demonstration of the effectiveness of deep learning in accurately predicting weather patterns, validated through comprehensive evaluation metrics and visualizations.
5. Contribution to the advancement of AI-driven solutions in weather forecasting, showcasing the potential for scalable and efficient prediction systems to aid in decision-making processes.

## **1.6 Organization of the Report**

### **Chapter 1: Introduction:**

Provides an overview of weather forecasting and its significance in decision-making. The chapter outlines the project's objectives, motivation, and the methodology used to develop and evaluate deep learning models for time-series weather prediction.

### **Chapter 2: Literature Review:**

Reviews existing approaches and methodologies for weather forecasting, focusing on the application of deep learning techniques like LSTMs, GRUs, and CNNs. The chapter identifies research gaps and highlights the need for improved accuracy in weather prediction models

### **Chapter 3: Methodology/Requirement Analysis & Design Specification:**

Explains the step-by-step process of data collection, preprocessing, model development, and evaluation. It details the design and implementation of the proposed deep learning models, including LSTM, GRU, 1D CNN, and Hybrid CNN-LSTM, along with the evaluation metrics used for performance assessment.

### **Chapter 4: Implementation:**

Describes the practical implementation of the models, including the configuration of training and testing datasets, hyperparameter tuning, and the execution of experiments. It also highlights the challenges faced during the implementation process and how they were addressed.

### **Chapter 5: Results and Analysis:**

Presents the results of the experiments conducted on the proposed models. The chapter includes detailed comparisons of model performances based on metrics like Mean Squared Error, Mean Absolute Error, R-squared, and regression accuracy. Visualization techniques, such as training vs. validation loss curves and distribution graphs, are used to support the analysis.

### **Chapter 6: Impact on Society, Environment, and Sustainability:**

Explores the broader implications of the project, such as the potential benefits of accurate weather forecasting for agriculture, disaster management, and environmental sustainability. It discusses how this research contributes to the development of AI-driven solutions that enhance societal resilience to weather-related challenges.

### **Chapter 7: Conclusion and Future Work:**

Summarizes the key findings of the research and emphasizes the importance of deep learning in weather prediction. The chapter identifies areas for improvement, such as optimizing hybrid models, and outlines potential directions for future research to enhance model scalability and real-time prediction capabilities.

# Chapter 2

## Background

This chapter explores the background of weather forecasting using machine learning, reviews existing research, identifies gaps in current approaches, and highlights the need for improved methodologies. It concludes by summarizing key findings to guide the proposed solution.

### 2.1 Introduction

The task of weather forecasting involves analyzing complex patterns and relationships within meteorological data to provide accurate predictions. Weather prediction plays a crucial role in agriculture, disaster management, and various industries, making it a significant area of study. Traditional methods, while effective to some extent, often struggle with the intricacies and non-linear nature of weather patterns. Recent advancements in deep learning, particularly recurrent neural networks (RNNs) and their variants, have provided powerful tools for sequential data analysis. These methods excel in capturing temporal dependencies, making them well-suited for forecasting tasks. Integrating advanced models such as LSTM, GRU, and hybrid architectures into weather prediction systems opens up possibilities for improved accuracy and efficiency, addressing the limitations of traditional forecasting methods.

### 2.2 Literature Review

Table 2.1: Summary of Literature Reviewed.

Author(s)	Year	Title	Methodology	Key Findings
Sue Ellen Haupt, Jim Cowie	2018	Machine Learning for Applied Weather Prediction	DI-Cast, Neural Networks	Improved forecasting, Big Data integration
Mark Holmstrom, Dylan Liu, Christopher Vo	2016	Machine Learning Applied to Weather Forecasting	Linear, Functional Regression	RMS error: 5.039-6.329°F
Sravani Nalluri, Somula Ramasubbarreddy, G. Kannayaram	2019	Weather Prediction Using Clustering Strategies in Machine Learning	Clustering Techniques (K-Means)	K-Means best; 0.01s

Shubham Madan, Praveen Kumar, Seema Rawat	2018	Analysis of Weather Prediction using Machine Learning & Big Data	Linear Regression, SVM	Accurate forecasting 5-day
Sebastian Scher, Gabriele Messori	2020	Predicting Weather Forecast Uncertainty with Machine Learning	Convolutional Neural Network	Correlation: ~0.33-0.28
R. Meenal, Prawin Angel Michael, D. Pamela.	2021	Weather Prediction Using Random Forest Machine Learning Model	Random Forest Algorithm	$R^2 = 0.97$ , MSE = 0.750
Vladimir M. Krasnopolsky, Michael S. Fox-Rabinovitz	2006	Complex Hybrid Models Combining Deterministic and Machine Learning Components for Numerical Climate Modeling and Weather Prediction	Neural Network Hybridization	~80x speed improvement
Naveen L., Mohan H. S.	2019	Atmospheric Weather Prediction Using Various Machine Learning Techniques: A Survey	ML Techniques Survey	Wavelet-SVM Best, RMSE 0.13
Nitin Singh, Saurabh Chaturvedi, Shamim Akhter	2019	Weather Forecasting Using Machine Learning Algorithm	Random Forest Classification	Accuracy: 87.90%
Muyideen AbdulRah eem, Joseph Bamidele Awotunde	2022	Weather Prediction Performance Evaluation on Selected Machine Learning	Decision Trees, k-NN, Logistic Regression	DT: 100%, LR: 93%, k-NN: 78%

		Algorithms		
--	--	------------	--	--

## 2.3 Gap Analysis

The field of weather forecasting has seen remarkable progress with the adoption of machine learning and deep learning techniques. However, there remain critical gaps that hinder the full potential of these technologies. Traditional statistical models and basic machine learning approaches, though widely used, often fail to capture the intricate, non-linear relationships in weather data. While advanced models like LSTMs and GRUs have been applied to address temporal dependencies, comparative studies across architectures are often missing, leaving the strengths and weaknesses of these models underexplored.

Another significant challenge lies in the limited availability of high-quality datasets for weather forecasting. Many studies rely on small datasets, which restrict the generalization capabilities of models. Additionally, insufficient data preprocessing and augmentation strategies often lead to overfitting, resulting in less reliable predictions in real-world scenarios.

Furthermore, the interpretability of deep learning models remains an area of concern. Weather prediction systems must provide not only accurate results but also understandable insights for stakeholders such as meteorologists and policymakers. However, many studies focus solely on improving accuracy metrics without considering how the models' predictions can be interpreted and utilized effectively.

Finally, the computational efficiency of models is often neglected. Many high-performing models require significant resources, making them unsuitable for real-time applications or deployment in resource-constrained environments. These challenges underscore the need for a comprehensive study that evaluates multiple architectures, incorporates robust preprocessing techniques, ensures scalability, and emphasizes both accuracy and interpretability.

This research addresses these gaps by leveraging LSTM, GRU, 1D CNN, and hybrid CNN-LSTM architectures, performing a thorough evaluation of their performance, and optimizing them for real-world applicability in weather forecasting.

## 2.4 Summary

In this chapter, we explored the foundational concepts and prior research relevant to weather forecasting using machine learning and deep learning techniques. We began by introducing the challenges associated with traditional weather prediction methods and the advantages of advanced AI-driven approaches. A comprehensive literature review highlighted the current state of research in this domain, showcasing the effectiveness of models like LSTMs, GRUs, and CNNs in capturing temporal and spatial dependencies within weather data.

Additionally, we conducted a gap analysis to identify key limitations in existing

studies, such as insufficient comparative evaluations, lack of interpretability, and limited focus on computational efficiency. These insights underline the need for a more holistic approach that not only achieves high accuracy but also ensures scalability, reliability, and usability in real-world applications.

This chapter sets the stage for the proposed methodology, which aims to bridge these gaps by leveraging advanced deep learning architectures, robust preprocessing techniques, and a detailed evaluation framework. The next chapter will delve into the specifics of the methodology adopted, including data preparation, model development, and performance evaluation strategies.

# Chapter 3

## Research Methodology

This chapter describes the methodology for weather prediction, covering data collection, preprocessing, feature extraction, and model development. It highlights the evaluation of models like LSTM, GRU, and 1D CNN, identifying the most accurate approaches for reliable weather forecasting.

### 3.1 Methodology

#### 3.1.1 Overview

This study adopts a systematic approach for weather prediction using recurrent neural networks and related deep learning techniques. The methodology is structured into several stages, including data preprocessing, model development, training, and evaluation. Each stage leverages advanced deep learning architectures to ensure accurate and robust predictions, addressing the challenges inherent in weather forecasting.

#### 3.1.2 Proposed Methodology/ System Design




Figure 3.1: Model Architecture

This study introduces a comprehensive methodology for weather forecast prediction using advanced deep learning techniques, incorporating recurrent neural networks (RNNs) such as LSTM, GRU, and CNN-based hybrid models. The methodology begins with data collection, utilizing a structured CSV dataset containing relevant weather features, including temperature, humidity, and pressure. Data preprocessing is performed to handle

missing values, normalize the data, and ensure consistency. The dataset is subsequently divided into training, validation, and testing splits for model development.

Feature extraction involves the use of sliding window techniques to create input-output sequences, enabling the models to capture temporal dependencies in the data. Initially, multiple models, including LSTM and GRU, are developed and trained. These models demonstrate strong performance, with LSTM achieving the highest accuracy of 83.44%. To explore further improvements, a hybrid CNN-LSTM model is implemented to combine the feature extraction capabilities of CNNs with the sequence modeling capabilities of LSTMs. However, this model shows limited performance, with an accuracy of 69.69%.

The evaluation of the models is conducted using metrics such as Mean Squared Error (MSE), Mean Absolute Error (MAE), R-squared, and Regression Accuracy. Additionally, visualization techniques, including training-validation loss curves, actual vs predicted plots, residual analysis, and distribution comparisons, are employed to gain deeper insights into the model performance. The study concludes by identifying LSTM and 1D CNN as the most effective models for weather forecast prediction. This systematic approach emphasizes the importance of RNNs in capturing sequential patterns in weather data for accurate forecasting.

## 3.2 Detailed Methodology

### 1. Data Collection

The dataset used in this study is a structured CSV file containing weather data with relevant features such as temperature, humidity, and pressure. These features are essential for understanding weather patterns and building predictive models.

### 2. Data Preprocessing

#### Normalization and Scaling

To ensure consistency and eliminate bias caused by different scales of features, normalization is applied. The Min-Max normalization technique is used to scale features to a range of [0, 1]:

$$x' = \frac{x - x_{\min}}{x_{\max} - x_{\min}}$$

Where  $x$  is the original value and  $X_{min}$  and  $X_{max}$  are the minimum and maximum value of the feature.

#### Handling Missing Values

Missing values are imputed using techniques like mean or median imputation, depending on the data distribution.

## Data Splitting

The dataset is divided into training, validation, and testing subsets. Typically, 80% of the data is used for training and validation, and the remaining 20% for testing.




Figure 3.2: Max and Min Temp




Figure 3.3: Precipitation over time




Figure 3.4: Wind speed over time




Figure 3.5: Weather condition frequency

### 3. Feature Extraction

#### Sliding Window Technique

To capture temporal dependencies, a sliding window is applied to create input-output sequences. For a window size  $w$  the input matrix  $\mathcal{X}$  and the output vector  $\mathcal{Y}$  are constructed as follows:

$$X_t = \{x_{t-w}, x_{t-w+1}, \dots, x_{t-1}\}, \quad y_t = x_t$$

Here,  $X_t$  represents the feature values over the previous  $w$  time steps, and  $Y_t$  is the target variable.

#### Sequence Preparation

The input sequences  $\mathcal{X}$  are reshaped to a 3D tensor of shape(samples, timesteps, features), which is required for deep learning models like LSTM and GRU.

#### Model Development

Multiple deep learning models are implemented to evaluate their performance for weather prediction:

##### 1. LSTM and GRU Models

These recurrent neural networks are designed to model sequential data by retaining long-term dependencies. The key equations for an LSTM cell are:

$$\begin{aligned} f_t &= \sigma(W_f \cdot [h_{t-1}, x_t] + b_f) \\ i_t &= \sigma(W_i \cdot [h_{t-1}, x_t] + b_i) \\ \tilde{C}_t &= \tanh(W_C \cdot [h_{t-1}, x_t] + b_C) \\ C_t &= f_t \odot C_{t-1} + i_t \odot \tilde{C}_t \\ o_t &= \sigma(W_o \cdot [h_{t-1}, x_t] + b_o) \\ h_t &= o_t \odot \tanh(C_t) \end{aligned}$$

Where  $f_t, i_t, o_t$  are the forget, input, and output gates,  $ct$  is the cell state and  $ht$  is the hidden state.

## 2. 1D CNN Model

Convolutional layers are applied to extract local patterns in the data. The output of a 1D convolution is given by:

$$y_i = \sum_{k=0}^{K-1} w_k \cdot x_{i+k} + b$$

Where  $w_k$  is the kernel weight,  $x_{i+k}$  is the input and  $b$  is the bias.

## 3. Hybrid CNN-LSTM Model

Combines the feature extraction capabilities of CNNs with the sequence modeling strengths of LSTMs to capture both spatial and temporal dependencies.

### Model Training

#### 1. Training Process

Models are trained on the training dataset with early stopping and checkpointing to prevent overfitting. The mean squared error (MSE) is used as the loss function:

$$\text{MSE} = \frac{1}{n} \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

Where  $y_i$  and  $\hat{y}_i$  are the actual and predicted values.

#### 2. Validation

Model performance is monitored on the validation set to tune hyperparameters and optimize model performance.

## Model Evaluation

The trained models are evaluated using multiple metrics:

### 1. Mean Absolute Error (MAE):

$$\text{MAE} = \frac{1}{n} \sum_{i=1}^n |y_i - \hat{y}_i|$$

### 2. R-squared ( $R^2$ ):

$$R^2 = 1 - \frac{\sum_{i=1}^n (y_i - \hat{y}_i)^2}{\sum_{i=1}^n (y_i - \bar{y})^2}$$

### 3. Regression Accuracy:

$$\text{Accuracy} = 100 - \text{MAPE}, \quad \text{where MAPE} = \frac{1}{n} \sum_{i=1}^n \left| \frac{y_i - \hat{y}_i}{y_i} \right| \times 100$$

### 4. Visualization:

- Performance is visualized using:
- Training-validation loss curves
- Actual vs predicted value plots
- Residual analysis
- Distribution comparison of actual and predicted values **Final**

## Model Selection

Based on evaluation metrics, the LSTM and 1D CNN models are identified as the most effective for weather prediction, achieving regression accuracies of 83.44% and 83.09%, respectively. The hybrid CNN-LSTM model demonstrated lower performance with a regression accuracy of 69.69%.

## 3.3 Project Plan

Task	Start Date	Duration	End Date
Data Collection	January 1, 2024	1 month	January 31, 2024
Data Preprocessing	February 1, 2024	2 months	March 31, 2024
Feature Extraction	April 1, 2024	1 month	April 30, 2024
Graph Construction	May 1, 2024	1.5 months	June 15, 2024

Model Development	June 16, 2024	2 months	August 15, 2024
Model Evaluation	August 16, 2024	1.5 months	September 30, 2024
Result Analysis	October 1, 2024	1 month	October 31, 2024
Report Writing	December 8, 2024	1 week	December 14, 2024
Final Submission	December 29, 2024	1 day	December 29, 2024

Table 3.1 : Project plan

### 3.4 Task Allocation

Task	Contributor(s)	Description
Data Collection	Self	Sourced and organized weather data from structured CSV files, ensuring completeness and accuracy.
Data Preprocessing	Self	Normalized and scaled data, handled missing values, addressed outliers, and split data into training, validation, and testing sets.
Feature Extraction	Self	Extracted key features for time-series analysis, applied sliding window techniques to prepare input-output sequences.
Model Development	Self	Implemented and fine-tuned models, including LSTM, GRU, 1D CNN, and Hybrid CNN-LSTM, ensuring robust configurations.
Model Evaluation	Self	Evaluated models using metrics such as MSE, MAE, R-squared, and Regression Accuracy; visualized results with graphs.
Result Analysis	Self	Analyzed model performance, compared results, and derived insights for inclusion in the report.
Report Writing	Self	Wrote, structured, and formatted the report, detailing methodology, results, and analysis.

Final Presentation Preparation	Self	Designed slides, created visualizations, and prepared content for the final project presentation.
--------------------------------	------	---

Table 3.2: Task allocation

### 3.5 Summary

In this chapter, we detailed the step-by-step methodology employed in the weather prediction project. Starting with data collection, structured CSV files containing weather-related features were acquired and carefully organized. The data preprocessing phase ensured data quality through normalization, handling of missing values, and splitting into training, validation, and testing sets. Feature extraction was performed using time-series techniques such as sliding windows to create meaningful input-output sequences.

We proceeded with model development, implementing various deep learning models, including LSTM, GRU, 1D CNN, and a Hybrid CNN-LSTM. Each model was trained and evaluated using performance metrics like Mean Squared Error (MSE), Mean Absolute Error (MAE), R-squared, and Regression Accuracy. The best-performing models were identified based on their evaluation results. Finally, insights derived from result analysis were integrated into the report, ensuring comprehensive documentation of the methodologies and findings. This chapter establishes the foundation for the subsequent analysis and results discussion.

# Chapter 4

## Implementation and Results

This chapter presents the implementation details and results of the proposed methodology. It includes the experimental setup, model evaluation metrics, and comparative analysis of different CNN-GNN models. The chapter highlights the superior performance of the ResNet18 + GIN model, achieving 98% accuracy, and provides a discussion on the outcomes and their implications.

### 4.1 Environment Setup

The implementation was carried out using a combination of local and cloud-based environments to ensure smooth training and evaluation processes. Initial code development and experimentation were conducted on a laptop with an Intel Core i3 11th Gen processor, 8 GB RAM, and a 256 GB NVMe SSD. For large-scale training and performance evaluations, Kaggle's cloud platform was utilized, leveraging its NVIDIA Tesla T4 GPU to enhance computational efficiency. The implementation relied on Python

3.12 as the primary programming language, alongside essential libraries such as TensorFlow and Keras for model development, NumPy and Pandas for data manipulation, Matplotlib and Seaborn for visualization, and Scikit-Learn for evaluation and preprocessing. This integrated setup provided a robust framework for effectively implementing, training, and validating the proposed models for weather prediction.

### 4.2 Performance / Comparative Analysis

#### 4.2.1 Evaluation Metrics

The performance of the models developed for weather prediction was assessed using the following evaluation metrics:

##### Mean Squared Error (MSE):

MSE measures the average squared difference between actual and predicted values. It penalizes larger errors more significantly, making it suitable for assessing prediction accuracy. A lower MSE indicates better model performance.

$$\text{MSE} = \frac{1}{n} \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

##### Mean Absolute Error (MAE):

MAE calculates the average of absolute differences between actual and predicted values. It is less sensitive to outliers than MSE. A lower MAE value

represents higher accuracy.

$$\text{MAE} = \frac{1}{n} \sum_{i=1}^n |y_i - \hat{y}_i|$$

**R-squared (R<sup>2</sup>):**

R<sup>2</sup> explains the proportion of variance in the actual values that the model can predict. It ranges from 0 to 1, with higher values indicating better fit.

$$R^2 = 1 - \frac{\sum_{i=1}^n (y_i - \hat{y}_i)^2}{\sum_{i=1}^n (y_i - \bar{y})^2}$$

**Regression Accuracy:**

Regression accuracy represents the model's ability to make accurate predictions relative to actual values. It is calculated as:

$$\text{Accuracy} = 100 - \text{MAPE}$$

where MAPE (Mean Absolute Percentage Error) is:

$$\text{MAPE} = \frac{1}{n} \sum_{i=1}^n \left| \frac{y_i - \hat{y}_i}{y_i} \right| \times 100$$

**Visualization Metrics:**

To complement numerical metrics, various visual tools, such as training vs. validation loss curves, actual vs. predicted value plots, residual plots, and distribution comparisons, were used to analyze model performance comprehensively. These visualizations provided deeper insights into model behavior and prediction quality.

#### 4.2.2 Model Performance Discussion

The proposed methodology for weather prediction involved implementing and evaluating four distinct models: LSTM, GRU, 1D CNN, and a Hybrid CNN-LSTM model. Each model's performance was analyzed using key metrics such as Mean Squared Error (MSE), Mean Absolute Error (MAE), R-squared (R<sup>2</sup>), and Regression Accuracy.

## 1. LSTM Model

The Long Short-Term Memory (LSTM) network, known for its ability to capture long-term dependencies in sequential data, achieved commendable performance. It recorded an MSE of 8.03, an MAE of 2.24, an  $R^2$  of 0.84, and a Regression Accuracy of 83.44%. The LSTM model demonstrated its strength in handling the temporal nature of weather data, capturing trends effectively. The training and validation loss curves showed steady convergence, indicating minimal overfitting.




Figure 4.1: Training and validation loss curve(LSTM)




Figure 4.2: Residuals vs Predicted values(LSTM)




Figure 4.3: Actual vs Predicted values (LSTM)




Figure 4.4: Distribution of actual vs Predicted values (LSTM)

## 2. GRU Model

The Gated Recurrent Unit (GRU), a computationally efficient alternative to LSTM, exhibited slightly lower performance than LSTM. It achieved an MSE of 9.16, an MAE of 2.39, an  $R^2$  of 0.82, and a Regression Accuracy of 81.72%. While GRU models can learn temporal patterns effectively, their slightly reduced complexity may have contributed to the marginally lower performance compared to LSTM. The residual plots showed a moderate spread of errors, emphasizing areas for improvement.




Figure 4.5: Training and validation loss curve(GRU)




Figure 4.6: Residuals vs Predicted values(GRU)




Figure 4.7: Actual vs Predicted values (GRU)




Figure 4.8: Distribution of actual vs Predicted values (GRU)

### 3. 1D CNN Model

The 1D Convolutional Neural Network (CNN), leveraging convolutional layers to extract features, emerged as one of the top-performing models. It achieved an MSE of 7.80, an MAE of 2.21, an  $R^2$  of 0.85, and a Regression Accuracy of 83.09%. This model's ability to identify local patterns in the weather data, combined with efficient training, contributed to its high accuracy. The comparison of actual vs. predicted values revealed a strong alignment, further supported by favorable residual distribution.




Figure 4.9: Training and validation loss curve(1D)




Figure 4.10: Residuals vs Predicted values(1D)




Figure 4.11: Actual vs Predicted values (1D)




Figure 4.12: Distribution of actual vs Predicted values (1D)

## 5. Hybrid CNN-LSTM Model

The Hybrid CNN-LSTM model, which combines the feature extraction capabilities of CNN with the sequential learning strengths of LSTM, did not perform as expected. It recorded an MSE of 35.83, an MAE of 5.06, an  $R^2$  of 0.29, and a Regression Accuracy of 69.69%. Despite the theoretical advantages of combining these architectures, the model struggled to generalize effectively, possibly due to overfitting or suboptimal parameter tuning. This highlights the need for further refinement in hybrid approaches for weather prediction.




Figure 4.13: Training and validation loss curve(HCL)




Figure 4.14: Residuals vs Predicted values(HCL)




Figure 4.15: Actual vs Predicted values (HCL)




Figure 4.16: Distribution of actual vs Predicted values (HCL)

### 4.3 Results and Discussion

Throughout the study, multiple models were implemented and evaluated for weather prediction, including LSTM, GRU, 1D CNN, and a Hybrid CNN-LSTM model. Each model exhibited varying levels of performance based on its ability to capture temporal patterns, feature relationships, and weather trends. The LSTM model emerged as one of the top-performing frameworks, achieving a Regression Accuracy of 83.44% with an MSE of 8.03 and an  $R^2$  of 0.84. Its strength in handling long-term dependencies and temporal patterns contributed to its high performance, making it particularly suitable for sequential weather data. The GRU model, while efficient, demonstrated slightly lower performance compared to LSTM. It achieved a Regression Accuracy of 81.72%, an MSE of 9.16, and an  $R^2$  of 0.82. The GRU model's relatively reduced complexity may have contributed to its marginally lower effectiveness in capturing intricate weather patterns.

The 1D CNN model delivered competitive results, achieving a Regression Accuracy of 83.09%, an MSE of 7.80, and an  $R^2$  of 0.85. Its ability to identify local patterns in the data made it highly effective, reinforcing the importance of feature extraction in weather prediction tasks. In contrast, the Hybrid CNN-LSTM model, which theoretically combines the strengths of CNN for feature extraction and LSTM for sequential learning, underperformed with a Regression Accuracy of 69.69%, an MSE of 35.83, and an  $R^2$  of 0.29. The model's inability to generalize effectively suggests potential challenges in balancing the hybrid architecture for this specific dataset.

These results highlight the LSTM and 1D CNN models as the most effective frameworks for weather prediction in this study. The findings underscore the importance of selecting appropriate models for sequential tasks and emphasize the need for further refinement and optimization in hybrid approaches to achieve robust and reliable performance.

Model	Architecture	Accuracy (%)	MSE	MAE	$R^2$
LSTM	Recurrent Neural Network (RNN)	83.44	8.03	2.24	0.84
GRU	Recurrent Neural Network (RNN)	81.72	9.16	2.39	0.82

1D CNN	Convolutional Neural Network	83.09	7.80	2.21	0.85
Hybrid CNN-LSTM	Hybrid Architecture	69.69	35.83	5.06	0.29

Table 4.1: Comparative model table




Figure 4.17 : Actual vs Predicted Values comparison for all models




Figure 4.18 : Residual Distribution Comparison for all Models




Figure 4.19 : Training and Validation Loss curves for All Models





Figure 4.20 : Regression Accuracy Comparison



Figure

4.21 : MSE Comparison

## 4.4 Summary

This chapter presented the performance evaluation and comparative analysis of the implemented models for weather prediction. Evaluation metrics such as Mean Squared Error (MSE), Mean Absolute Error (MAE), R-squared ( $R^2$ ), and Regression Accuracy were utilized to measure the effectiveness of each model. The LSTM and 1D CNN models demonstrated superior performance, with accuracies of 83.44% and 83.09%, respectively. The GRU model achieved a slightly lower accuracy of 81.72%.

However, the Hybrid CNN-LSTM model performed suboptimally, with an accuracy of 69.69%, highlighting its limited effectiveness for this task.

The discussion also included graphical representations such as training-validation loss curves, actual versus predicted value plots, residual analysis, and distribution comparisons to provide a deeper understanding of each model's performance. The results emphasized the robustness of the LSTM and 1D CNN models for time-series weather prediction, establishing them as the most reliable architectures for this project.

# Chapter 5

## Engineering Standards and Design Challenges

This chapter presents the implementation details and results of the proposed methodology. It includes the experimental setup, model evaluation metrics, and a comparative analysis of different models, including LSTM, GRU, 1D CNN, and Hybrid CNN-LSTM. The chapter highlights the superior performance of the LSTM model, achieving 83.44% accuracy, and provides a discussion on the outcomes and their implications for weather prediction.

### 5.1 Compliance with the Standards

#### 5.1.1 Software Standards

This research project adheres to recognized software standards to ensure robust development, scalability, and efficiency. The implementation was primarily carried out on Kaggle Notebook, leveraging its cloud-based environment and free access to GPU resources, including NVIDIA Tesla T4, for efficient model training and evaluation. Additionally, a personal laptop with an Intel Core i3 11th Gen processor, 8GB RAM, and a 256GB NVMe SSD was utilized for initial code development and debugging.

Python 3.12 was chosen as the programming language due to its extensive library ecosystem, including NumPy, Pandas, Matplotlib, and TensorFlow/Keras, which facilitated data preprocessing, statistical analysis, model development, and visualization. These tools ensured modularity, maintainability, and adherence to modern software engineering practices.

The development process followed standard software engineering principles, emphasizing modular design, systematic testing, and clear documentation. Kaggle Notebook was selected for its scalability and built-in integration with datasets, making it ideal for iterative experimentation and model evaluation. This environment also allowed for the efficient handling of large datasets and computationally intensive processes required for weather prediction models.

The project prioritized accuracy and reproducibility by ensuring that all software components adhered to best practices, enhancing both the reliability and scalability of the developed solution.

#### 5.1.2 Hardware Standards

The hardware utilized for this project was selected to balance efficiency, accessibility, and

computational capability. Initial development and debugging were conducted on a personal laptop equipped with an Intel Core i3 11th Gen processor, 8GB RAM, and a 256GB NVMe SSD. While this setup provided sufficient performance for smaller-scale operations, such as data preprocessing and basic model testing, it had limitations in handling larger datasets and training deep learning models.

To address these limitations, Kaggle Notebook was leveraged for training and evaluating models. Kaggle's infrastructure provided access to NVIDIA Tesla T4 GPUs, offering high-performance computational power necessary for running computationally intensive tasks such as training LSTM, GRU, 1D CNN, and Hybrid CNN-LSTM models. The inclusion of cloud-based GPU resources significantly reduced training time and allowed for iterative model optimization.

This combination of local hardware for initial stages and cloud resources for large-scale experiments ensured an efficient and cost-effective approach to achieving the project's objectives while maintaining high computational standards.

### **5.1.3 Communication Standards**

This project adheres to established communication standards to ensure efficient data processing and seamless interaction between various components. The primary communication methods revolve around the interaction between data files, processing frameworks, and cloud-based platforms.

The dataset was handled in CSV format, which is a universally recognized standard for structured data storage and transfer. Libraries such as Pandas and NumPy were utilized to read, manipulate, and analyze the data, ensuring consistent communication between data preprocessing, feature extraction, and model development stages.

For model training and evaluation, Kaggle Notebook was employed, leveraging its cloud-based resources and NVIDIA Tesla T4 GPUs. The platform ensures secure communication protocols, such as HTTPS, for data transfer and remote computations, ensuring data integrity and reliability.

Visualization of results and performance metrics was carried out using Matplotlib and Seaborn, which adhere to standardized data visualization practices, ensuring clarity and precision in result interpretation and communication.

These standards collectively ensured effective and reliable communication between all stages of the project, facilitating the smooth execution of the proposed methodology.

## **5.2 Impact on Society, Environment and Sustainability**

### **5.2.1 Impact on Life**

The proposed weather prediction framework has the potential to significantly impact lives

by enhancing the accuracy and reliability of weather forecasts. Accurate weather predictions can aid individuals, farmers, and businesses in making informed decisions, such as preparing for adverse weather conditions, optimizing agricultural planning, and ensuring safety during natural disasters.

The use of advanced AI models in this project reduces reliance on traditional manual forecasting methods, enabling timely predictions with higher precision. This can help communities better prepare for unexpected events like storms, droughts, or floods, ultimately minimizing risks to life and property. Additionally, the project emphasizes accessibility by leveraging efficient and scalable solutions, ensuring that reliable weather forecasts are available to a broader population.

### **5.2.2 Impact on Society & Environment**

The proposed weather prediction framework contributes positively to society by enabling accurate and timely weather forecasts, which can aid in disaster preparedness and mitigation efforts. Communities can better plan for extreme weather events, potentially saving lives and reducing economic losses. This enhanced capability can improve public safety, agricultural productivity, and infrastructure resilience.

From an environmental perspective, accurate weather predictions can support sustainable practices by optimizing resource usage in agriculture, energy production, and water management. For instance, farmers can adjust irrigation schedules based on predicted rainfall, reducing water wastage and promoting sustainable agriculture. Additionally, improved weather forecasting can assist in early identification of climate trends, contributing to broader environmental conservation efforts.

By leveraging AI for weather predictions, the project aligns with global sustainability goals, fostering societal well-being while minimizing the ecological footprint of traditional forecasting methods.

### **5.2.3 Ethical Aspects**

This project adheres to strict ethical principles to ensure the responsible use of technology in weather prediction. The data used in the study was sourced from publicly available repositories, ensuring compliance with data privacy and intellectual property regulations. No sensitive or personally identifiable information was involved in the analysis, maintaining data integrity and ethical standards.

The methodology emphasizes transparency and fairness by using unbiased algorithms that are rigorously evaluated for performance and accuracy. This ensures that the predictions made by the models are reliable and do not favor any specific region or demographic.

Furthermore, the project avoids over-reliance on computational resources, promoting sustainability and reducing environmental impact. The intention is to use AI technology as a tool to benefit society without introducing ethical dilemmas, such as the misuse of predictions for commercial exploitation or geopolitical advantages.

### **5.2.4 Sustainability Plan**

The sustainability plan for this project focuses on long-term viability, environmental

consciousness, and societal benefits. Key aspects of the plan include:

**Energy Efficiency:** Leveraging optimized machine learning models that require minimal computational power, the project ensures reduced energy consumption, especially during training and evaluation phases. By utilizing cloud-based platforms like Kaggle with pre-configured GPUs, resource usage is minimized.

**Scalability:** The methodology and models are designed to accommodate larger datasets and more complex features in the future. This adaptability ensures the system remains relevant as weather prediction datasets grow in size and diversity.

**Reusability:** The project employs modular coding practices, allowing components such as data preprocessing pipelines and model architecture to be reused or adapted for other predictive tasks. This reduces the need for redundant development efforts.

**Social Benefit:** By providing accurate weather predictions, the project contributes to better decision-making in agriculture, disaster management, and energy distribution. This promotes societal resilience and reduces vulnerabilities caused by climatic uncertainties.

**Continuous Improvement:** Regular updates to the models based on new data and advances in AI techniques will ensure the system stays effective and sustainable over time, fostering a long-term impact on weather forecasting practices.

## 5.3 Project Management and Financial Analysis

### 5.3.1 Project Management

The project was managed using a structured and iterative approach, focusing on efficient resource utilization and timely task completion. Tasks such as data collection, preprocessing, model development, and evaluation were planned with specific timelines and milestones. Cloud-based platforms like Google Colab and Kaggle were utilized for their computational resources, ensuring cost-effectiveness and efficiency. Regular progress reviews helped address challenges, while comprehensive documentation captured methodologies and findings, ensuring transparency and enabling future replication of the work. This approach ensured the project's successful execution within the allocated timeframe and resources.

### 5.3.2 Financial Analysis

Item	Cost (BDT)	Purpose
Machine Learning course	7,000	For machine learning skills
Hardware upgrade (Ram)	3000	For enhance performance
Application and subscription	4000	For better model development and design
<b>Total</b>	<b>14000</b>	

Table 5.1 : Financial Analysis

## 5.4 Complex Engineering Problem

### 5.4.1 Complex Problem Solving

Table 5.2: Mapping with complex problem solving.

EP1 Dept of Knowled ge	EP2 Range Of Conflicting Requireme nts	EP3 Depth of Analys is	EP4 Familiari ty of Issues	EP5 Extent Of Applicab leCodes	EP6 Extent Of Stake- holder Involveme nt	EP7 Interdepen dence
✓	✓	✓	✓	✓	✓	✓

#### EP1 – Depth of Knowledge

This project demonstrates substantial expertise by leveraging advanced deep learning techniques, including Long Short-Term Memory (LSTM), Gated Recurrent Units (GRU), 1D Convolutional Neural Networks (1D CNN), and Hybrid CNN-LSTM models, for weather prediction. The use of time-series analysis methods, such as sliding window techniques, and the handling of structured weather data requires a solid understanding of sequence modeling and data preprocessing. The integration of various models, alongside their evaluation and comparison, reflects a deep grasp of machine learning and its application in climate science.

#### EP2 – Range of Conflicting Requirements

Balancing accuracy, computational efficiency, and resource limitations was a critical aspect of this project. High-accuracy weather prediction models required extensive preprocessing and training, yet computational resources, particularly on a local machine, posed constraints. By using cloud-based solutions such as Kaggle GPU, the project achieved a balance between performance and resource utilization. The Hybrid CNN-LSTM model, while complex, was explored as a potential solution, though simpler models like LSTM and 1D CNN outperformed it in accuracy and efficiency, highlighting the project's ability to navigate such trade-offs.

#### EP3 – Depth of Analysis

The methodology incorporates rigorous analysis at every stage, from data preprocessing to model evaluation. Data preprocessing involved handling missing values, outliers, and normalization to ensure consistency. Comprehensive evaluation metrics, including Mean Squared Error (MSE), Mean Absolute Error (MAE), R-squared, and Regression Accuracy, were employed to compare model performances. Visualizations such as training-validation loss curves, residual plots, and actual vs. predicted values provided detailed insights into model behavior, showcasing a systematic and analytical approach to achieving project objectives.

#### **EP4 – Familiarity of Issues**

This project addresses challenges specific to time-series forecasting, such as sequence modeling and handling temporal dependencies in weather data. Issues like variable weather patterns and noise in recorded data add complexity to the task. By integrating LSTM and GRU models, known for their ability to capture temporal relationships, the project tackles these challenges effectively. While time-series analysis is a well-studied domain, applying these techniques to weather forecasting with a focus on resource constraints presents unique and innovative aspects.

#### **EP5 – Extent of Applicable Codes**

The implementation adhered to best practices in software engineering, using Python and essential libraries such as TensorFlow, NumPy, Pandas, and Matplotlib. Code modularity and readability were ensured throughout the project. Moreover, cloud-based tools like Kaggle provided scalable resources for training and evaluation, aligning with modern practices in AI development. Ethical coding standards, such as proper data handling and transparency in reporting results, were maintained.

#### **EP6 – Extent of Stakeholder Involvement**

As a solo endeavor, the project directly addresses the needs of stakeholders such as meteorologists, researchers, and the general public who rely on accurate weather predictions. The design prioritizes interpretability and accuracy, ensuring that the models are practical for real-world applications. Future scalability options are also considered, enhancing the project’s relevance to broader audiences.

#### **EP7 – Interdependence**

This project highlights interdependence by integrating multiple components, including data preprocessing, feature extraction, model development, and evaluation. Each stage relies on the quality of outputs from the previous stages, emphasizing the interconnected nature of the workflow. The use of LSTM and GRU models to capture temporal dependencies and their integration with sliding window techniques demonstrates the synergy between preprocessing and model architecture in achieving accurate predictions.

#### **Mapping with Knowledge Profile for EP1**

Table 5.3: Mapping with knowledge Profile.

K3 Engineering Fundamentals	K4 Specialist Knowledge	K5 Engineering Design	K6 Engineering Practice	K8 Research Literature
✓	✓	✓	✓	✓

### **K3 - Engineering Fundamentals**

This project applies fundamental engineering principles from machine learning and time-series analysis to develop robust weather prediction models. The use of advanced neural networks like Long Short-Term Memory (LSTM), Gated Recurrent Units (GRU), and 1D Convolutional Neural Networks (1D CNN) exemplifies the integration of engineering fundamentals. Techniques like sliding window processing and feature extraction highlight the reliance on mathematical and computational principles to model temporal dependencies in weather data.

### **K4 - Specialist Knowledge**

Specialist knowledge in sequence modeling and time-series forecasting was crucial for the success of this project. Understanding the unique properties of LSTM and GRU architectures, such as their ability to capture long-term dependencies in sequential data, was essential. Expertise in data preprocessing, including normalization, handling missing values, and addressing outliers, further ensured the quality of the input data. This specialized knowledge was critical to improving model accuracy and stability.

### **K5 - Engineering Design**

The project involved the systematic design of a comprehensive pipeline for weather prediction. This includes preprocessing raw weather data, designing input-output sequences for time-series models, and implementing multiple neural network architectures. Each model was meticulously configured with appropriate hyperparameters, loss functions, and optimizers to achieve optimal performance. The selection of simpler models like LSTM and GRU over more complex hybrid approaches demonstrates careful design considerations for balancing accuracy, efficiency, and interpretability.

### **K6 - Engineering Practice**

The project adhered to practical engineering standards through the use of industry-grade tools and platforms. Python-based libraries like TensorFlow, NumPy, Pandas, and Matplotlib were utilized for preprocessing, model development, and evaluation. Training and testing were conducted on Kaggle's cloud-based environment, leveraging GPU resources for computational efficiency. These practices ensured that the implementation was both scalable and aligned with best practices in AI development.

### **K8 - Research Literature**

The project builds upon an extensive review of literature in time-series analysis and weather forecasting. It integrates state-of-the-art methods, such as LSTM and GRU, and evaluates their performance against simpler and hybrid models. By conducting comparative analyses, the project contributes to the ongoing research in weather prediction, providing insights into the effectiveness of different neural network architectures for time-series forecasting.

This mapping highlights the project’s alignment with engineering principles, showcasing its depth of knowledge, systematic design, and contribution to research and practice.

## 5.4.2 Engineering Activities

In this section, provide a mapping with engineering activities. For each mapping add subsections to put rationale (Use Table 5.3).

Table 5.4: Mapping with complex engineering activities.

EA1 Range of re- sources	EA2 Level of Interaction	EA3 Innovation	EA4 Consequences for society and environment	EA5 Familiarity
✓	✓	✓	✓	✓

### EA1 - Range of Resources

This project utilized a diverse range of computational resources to implement and evaluate weather prediction models. Primary development and training were conducted on Kaggle Notebooks, utilizing NVIDIA GPUs for efficient processing of deep learning models like LSTM, GRU, and 1D CNN. Preprocessing and debugging tasks were carried out on a local machine equipped with an Intel Core i3 processor, 8GB RAM, and a 256GB NVMe SSD, ensuring accessibility and cost-effectiveness. The combination of cloud-based GPU resources and local computational tools allowed for seamless handling of time-series data and model evaluations.

### EA2 - Level of Interaction

The project demonstrated a high level of interaction between various components of the workflow. Sequential weather data was preprocessed and transformed into input-output sequences for time-series models, requiring precise alignment of features. The iterative training of multiple models and their evaluation through comparative metrics further emphasized interaction between data, computational resources, and model configurations. This interconnected approach simulated real-world challenges in building and deploying machine learning solutions for predictive tasks.

### EA3 – Innovation

Innovation played a key role in the project by incorporating advanced deep learning techniques for weather forecasting. Models like LSTM and GRU were implemented to capture long-term dependencies, while 1D CNN offered an innovative perspective on extracting spatial features from time-series data. Although the hybrid CNN-LSTM model did not perform as expected, it demonstrated a novel attempt to combine temporal and spatial learning capabilities. The successful application of LSTM and GRU models with high accuracy underscores the project's contribution to advancing time-series forecasting methodologies.

#### **EA4 - Consequences for Society and Environment**

The project holds significant implications for society and the environment by improving the accuracy of weather predictions. Enhanced forecasting can aid in disaster preparedness, agricultural planning, and resource management, directly benefiting communities and mitigating the impacts of extreme weather events. The use of energy-efficient computational resources, like cloud-based GPUs, aligns with environmentally sustainable practices while maintaining accessibility for researchers and developers in resource-constrained settings.

#### **EA5 – Familiarity**

The project balanced familiarity with advanced techniques by integrating established deep learning models, such as LSTM and GRU, with emerging approaches like hybrid architectures. Familiar preprocessing methods, such as normalization and sliding window techniques, ensured data consistency, while the implementation of state-of-the-art models demonstrated the project's ability to adapt and innovate. This combination of established knowledge and cutting-edge methodologies reflects the robustness and reliability of the project's design and implementation.

### **5.5 Summary**

This chapter explored the compliance of the project with various software, hardware, and communication standards, ensuring a robust and ethical foundation for implementation. It detailed the societal, environmental, and ethical impacts of the project, emphasizing its potential to improve weather forecasting and its broader implications for disaster management and resource planning. Additionally, sustainability measures were highlighted to ensure long-term applicability, and the project's management and financial analysis demonstrated its feasibility and cost-effectiveness. Mapping the project with engineering knowledge and activities further showcased its depth, innovation, and alignment with real-world applications, making it a comprehensive and impactful initiative.

# Chapter 6

## Conclusion

This chapter highlights the standards and protocols followed throughout the project, including compliance with software and hardware requirements and the effective use of communication tools. It addresses challenges like optimizing computational resources, ensuring scalability, and upholding ethical and environmental responsibilities. The chapter concludes with an evaluation of the project's alignment with complex engineering activities, showcasing its innovative approach to weather forecasting and its broader societal and environmental impact.

### 6.1 Summary

This project successfully explored the application of deep learning techniques for weather forecasting, focusing on LSTM, GRU, 1D CNN, and Hybrid CNN-LSTM models. A systematic methodology was employed, starting from data preprocessing and feature extraction to model development, evaluation, and result analysis. The project highlighted the superior performance of LSTM and 1D CNN models, achieving high accuracy and efficiency in predictions, while the Hybrid CNN-LSTM model faced challenges in delivering optimal results. This study underscores the potential of AI-driven approaches for enhancing weather forecasting, providing a foundation for further advancements in this domain.

### 6.2 Limitation

**Hybrid Model Performance:** The Hybrid CNN-LSTM model underperformed compared to standalone LSTM and 1D CNN models, indicating the need for further exploration and optimization of hybrid architectures.

**Dataset Constraints:** The dataset used was limited in its representation of diverse climatic conditions and geographical regions, which may affect the generalizability of the models to broader contexts.

**Computational Challenges:** Limited computational resources restricted the exploration of more advanced architectures, extended training periods, or the inclusion of additional features in the models.

**Real-Time Predictions:** The lack of integration with real-time weather data limits the direct applicability of the models for real-world, dynamic forecasting scenarios.

**External Factors:** The models did not account for external influences such as seasonal trends, geographical factors, or extreme weather events, which could improve prediction accuracy. Addressing these limitations in future work can further enhance the reliability, scalability, and clinical relevance of the proposed framework.

## 6.3 Future Work

Building upon the findings and addressing the limitations of this project, the following directions are proposed for future work:

**Optimization of Hybrid Models:** Further research into hybrid architectures, incorporating advanced components such as attention mechanisms or transformer-based networks, to enhance performance.

**Dataset Expansion:** Collecting and integrating more extensive datasets from diverse regions and weather conditions to improve the robustness and adaptability of the models. **Real-Time Integration:** Developing a dynamic system capable of processing and predicting weather conditions in real-time, enhancing practical applicability.

**Feature Engineering:** Including additional features such as wind speed, solar radiation, or geographic and seasonal attributes to improve model precision and relevance.

**Deployment and Accessibility:** Creating a user-friendly interface, API, or mobile application for real-world usage, enabling end-users to access weather predictions seamlessly.

**Sustainability Focus:** Exploring energy-efficient models and eco-friendly computational practices to align the project with environmental sustainability goals.

**Collaboration and Scalability:** Engaging with meteorological agencies and research institutions to refine and scale the system for large-scale deployment and collaborative applications in weather prediction.

# References

- [1] **S. E. Haupt, J. Cowie, S. Linden, T. McCandless, B. Kosovic, and S. Alessandrini**, "Machine Learning for Applied Weather Prediction," 2018.
- [2] **M. Holmstrom, D. Liu, and C. Vo**, "Machine Learning Applied to Weather Forecasting," 2016.
- [3] **S. Nalluri, S. Ramasubbareddy, and G. Kannayaram**, "Weather Prediction Using Clustering Strategies in Machine Learning," *Proceedings of the International Conference on Emerging Technologies in Engineering and Science*, 2019.
- [4] **S. Madan, P. Kumar, S. Rawat, and T. Choudhury**, "Analysis of Weather Prediction using Machine Learning & Big Data," *2018 IEEE International Conference on Computing, Communication, and Automation (ICCCA)*, 2018, pp. 1-6.
- [5] **S. Scher and G. Messori**, "Predicting Weather Forecast Uncertainty with Machine Learning," *Environmental Research Letters*, vol. 15, no. 12, 2020.
- [6] **N. Singh, S. Chaturvedi, and S. Akhter**, "Weather Forecasting Using Machine Learning Algorithm," *2019 IEEE International Conference on Signal Processing and Communication (ICSPC)*, 2019.
- [7] **M. AbdulRaheem, J. B. Awotunde, A. E. Adeniyi, I. D. Oladipo, and S. O. Adekola**, "Weather Prediction Performance Evaluation on Selected Machine Learning Algorithms," *IAES International Journal of Artificial Intelligence (IJ-AI)*, vol. 11, no. 4, pp. 1535–1544, Dec. 2022.
- [8] **V. M. Krasnopolsky and M. S. Fox-Rabinovitz**, "Complex Hybrid Models Combining Deterministic and Machine Learning Components for Numerical Climate Modeling and Weather Prediction," 2006.
- [9] **Z. Ben-Bouallegue et al.**, "The Rise of Data-Driven Weather Forecasting," *arXiv preprint arXiv:2307.10128*, 2023.
- [10] **L. Gan, X. Man, C. Zhang, and J. Shao**, "EWMoE: An Effective Model for Global Weather Forecasting with Mixture-of-Experts," *arXiv preprint arXiv:2405.06004*, 2024.
- [11] **O. C. Pasche, J. Wider, Z. Zhang, J. Zscheischler, and S. Engelke**, "Validating Deep- Learning Weather Forecast Models on Recent High-Impact Extreme Events," *arXiv preprint arXiv:2404.17652*, 2024.

- [12] **A. B. Agarwal, R. Rajesh, and N. Arul**, "Spatially-Resolved Hyperlocal Weather Prediction and Anomaly Detection Using IoT Sensor Networks and Machine Learning Techniques," *arXiv preprint arXiv:2310.11001*, 2023.
- [13] **N. L. Mohan and H. S. Naveen**, "Atmospheric Weather Prediction Using Various Machine Learning Techniques: A Survey," 2019.
- [14] **A. Kadam, S. Idhate, G. Sonawane, R. Sathe, and P. Gundale**, "Weather Prediction Using Machine Learning," *International Journal of Creative Research Thoughts (IJCRT)*, 2023.
- [15] **S. Madan, P. Kumar, S. Rawat, and T. Choudhury**, "Analysis of Weather Prediction using Machine Learning & Big Data," *2018 IEEE International Conference on Computing, Communication, and Automation (ICCCA)*, 2018, pp. 1-6.
- [16] **N. Singh, S. Chaturvedi, and S. Akhter**, "Weather Forecasting Using Machine Learning Algorithm," *2019 IEEE International Conference on Signal Processing and Communication (ICSPC)*, 2019.
- [17] **M. Raissi, P. Perdikaris, and G. E. Karniadakis**, "Physics-Informed Neural Networks: A Deep Learning Framework for Solving Forward and Inverse Problems Involving Nonlinear Partial Differential Equations," *Journal of Computational Physics*, vol. 378, pp. 686-707, 2019.
- [18] **F. S. Oktem, O. F. Kar, C. D. Bezek, and F. Kamalabadi**, "High-Resolution Multi- Spectral Imaging with Diffractive Lenses and Learned Reconstruction," *IEEE Transactions on Computational Imaging*, vol. 7, pp. 1-12, 2021.
- [19] **M. Bernhardt, V. Vishnevskiy, R. Rau, and O. Goksel**, "Training Variational Networks with Multidomain Simulations: Speed-of-Sound Image Reconstruction," *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, vol. 67, no. 12, pp. 2510-2521, 2020.
- [20] **R. Lam et al.**, "Learning Skillful Medium-Range Global Weather Forecasting," *Science*, vol. 382, no. 6667, 2023.

Amal  
12/01/25

# rajon defence pre defence\_removed\_removed.pdf

## ORIGINALITY REPORT

<b>20%</b> SIMILARITY INDEX	<b>14%</b> INTERNET SOURCES	<b>10%</b> PUBLICATIONS	<b>10%</b> STUDENT PAPERS
--------------------------------	--------------------------------	----------------------------	------------------------------

## PRIMARY SOURCES

- 1** Submitted to Daffodil International University **3%**  
Student Paper
- 2** [www.mdpi.com](http://www.mdpi.com) **1%**  
Internet Source
- 3** Submitted to United International University **1%**  
Student Paper
- 4** Leon, Javier. "Forecasting Imported Fruit Prices in the United States Using Neural Networks", Northcentral University, 2024 **1%**  
Publication
- 5** [bura.brunel.ac.uk](http://bura.brunel.ac.uk) **1%**  
Internet Source
- 6** H.L. Gururaj, Francesco Flammini, S. Srividhya, M.L. Chayadevi, Sheba Selvam. "Computer Science Engineering", CRC Press, 2024 **1%**  
Publication
- 7** Vivek S. Sharma, Shubham Mahajan, Anand Nayyar, Amit Kant Pandit. "Deep Learning in **<1%**